


AMIKON TECHNICAL INTELLIGENCE

Product Data Sheet

Bently Nevada 330904-00-10-50-02-05

Metric M8X1 armored NSv proximity probe



PRODUCT	THREAD	TOTAL LENGTH	SYSTEM
3300 XL NSv Proximity Transducer System	M8X1	5.0 m	3300 XL NSv Proximity Transducer System

Bently Nevada 330904-00-10-50-02-05 is a Metric M8X1 armored NSv proximity probe used as the sensing or signal component in the matching 3300 XL NSv Proximity Transducer System system. Complete measurement requires compatible system components and the exact ordered electrical or loop configuration.

01 CURRENT PAGE PARAMETERS

Product Model	330904-00-10-50-02-05
Product Parameters	Metric M8X1 armored NSv proximity probe; M8X1; stainless steel armor
Tariff Code	9031809090
Place of shipment	Xiamen, China
Estimated Shipping Size	16.0 x 12.0 x 4.0 cm
Product Type	3300 XL NSv Proximity Transducer System
Case Thread	M8X1
Unthreaded Length	0 mm
Total Length	5.0 m
Cable and Connector	ClickLoc, standard cable
Estimated Probe Temperature Range	Refer to official manufacturer datasheet
Series-level Typical Weight	0.15 kg

Source scope: official Bently Nevada 147385 Rev. R, current product record, tariff and shipment fields. Technical configuration is limited to this exact model.

02 ORDERING CODE VERIFICATION

330904	Metric M8X1 armored NSv proximity probe
00	0 mm unthreaded length
10	100 mm overall case length
50	5.0 m total length
02	ClickLoc, standard cable
05	Multiple approvals

03 SYSTEM ROLE AND APPLICATIONS

The ordered 330904-00-10-50-02-05 configuration is used only with the compatible 3300 XL NSv Proximity Transducer System system. Maintain the specified system length, mounting, connector or output, and approval option.

- Radial vibration measurement on small shafts
- Radial position measurement in tight installations
- Axial thrust position measurement on small targets
- Tachometer and zero-speed measurement

04 OFFICIAL INSTALLATION FACTS

- Use the specified M8X1 mounting configuration.
- Maintain the ordered 5.0 m system length.
- Preserve ClickLoc, standard cable and protect all connections.
- Use the manufacturer drawing and controlled procedure for installation.

05 OFFICIAL DOCUMENTATION

[3300 XL NSv Proximity Transducer System System Datasheet - 147385 Rev. R](#)

Controlled references remain in the official data sheet and manufacturer documentation. Obtain current revisions through the manufacturer media library.

AMIKON PRODUCT SUPPORT

Amikon Limited

INFO@AMIKON.CN