

AMIKON TECHNICAL INTELLIGENCE

Product Data Sheet

Siemens 6ES7288-1SR30-0AA1
SIMATIC S7-200 SMART CPU SR30 AC/DC/Relay

PRODUCT	POWER	ONBOARD I/O	MEMORY
CPU SR30	85-264 V AC	18 DI / 12 relay DQ	30 KB

Siemens 6ES7288-1SR30-0AA1 is a SIMATIC S7-200 SMART CPU SR30 compact PLC with 18 integrated 24 V DC digital inputs and 12 relay outputs rated up to 2 A. The controller uses an 85-264 V AC supply and provides Ethernet and RS485 communication for small automation applications.

01

CURRENT PAGE PARAMETERS

Product Model	6ES7288-1SR30-0AA1
Product Type	SIMATIC S7-200 SMART CPU SR30
Power Supply	85-264 V AC, 47-63 Hz
Digital Inputs	18 integrated, 24 V DC
Relay Outputs	12 integrated, 2 A
Program/Data Memory	30 KB
Communication	Industrial Ethernet and RS485
Dimensions	110 x 100 x 81 mm
Approximate Weight	0.435 kg
Maximum Power Loss	14 W
Programming	STEP 7-Micro/WIN SMART
Commodity Code	85371091

Source scope: official Siemens Industry Mall product data and SIMATIC S7-200 SMART System Manual V2.8, A5E03822230-AL.

02

TECHNICAL SUMMARY

Article Number	6ES7288-1SR30-0AA1
CPU Designation	CPU SR30 AC/DC/Relay
Mounting	Standard DIN rail
Sensor Power	24 V DC, 300 mA max.
Input Current	4 mA per used digital input
Ethernet	10/100 Mbit/s
Serial Interface	RS485
Operating Temperature	0 to 55 deg C horizontal
Storage / Transport	-40 to 70 deg C
Relative Humidity	95% at 25 deg C, non-condensing
Installation Altitude	Up to 2000 m
Product Lifecycle	Active product; verify current Siemens PLM status

03

DOCUMENT CONTROL

Use the current Siemens product datasheet, S7-200 SMART system manual, electrical installation rules, and project-specific safety documentation. This Amikon document is a formatted reference and does not replace controlled Siemens instructions.