

AMIKON TECHNICAL INTELLIGENCE

Product Data Sheet

Bently Nevada 330101-00-44-15-02-CN
3/8-24 UNF standard-mount proximity probe



PRODUCT	THREAD	TOTAL LENGTH	SYSTEM
3300 XL 8 mm Proximity Transducer System	3/8-24 UNF	1.5 m total length	3300 XL 8 mm Proximity Transducer System

Bently Nevada 330101-00-44-15-02-CN is a 3/8-24 UNF standard-mount proximity probe used as the sensing or signal component in the matching 3300 XL 8 mm Proximity Transducer System system. Complete measurement requires compatible system components and the exact ordered electrical or loop configuration.

01 CURRENT PAGE PARAMETERS

Product Model	330101-00-44-15-02-CN
Product Parameters	3/8-24 UNF standard-mount proximity probe; 3/8-24 UNF; without armor
Tariff Code	9031809090
Place of shipment	Xiamen, China
Estimated Shipping Size	150 x 1.52 x 1.52 cm
Product Type	3300 XL 8 mm Proximity Transducer System
Case Thread	3/8-24 UNF
Unthreaded Length	0.0 in unthreaded length
Total Length	1.5 m total length
Cable and Connector	Miniature ClickLoc connector; standard cable
Estimated Probe Temperature Range	Refer to official manufacturer datasheet
Series-level Typical Weight	0.485 kg

Source scope: official Bently Nevada 141194 Rev. AM, current product record, tariff and shipment fields. Technical configuration is limited to this exact model.

02 ORDERING CODE VERIFICATION

330101	3/8-24 UNF probe without armor
00	0.0 in unthreaded length
44	4.4 in overall case length
15	1.5 m total length
02	ClickLoc connector with standard cable
CN	Country-specific approval suffix

03 SYSTEM ROLE AND APPLICATIONS

The ordered 330101-00-44-15-02-CN configuration is used only with the compatible 3300 XL 8 mm Proximity Transducer System system. Maintain the specified system length, mounting, connector or output, and approval option.

- Radial vibration measurement
- Axial shaft-position measurement
- Differential-expansion measurement
- Keyphasor phase-reference measurement

04 OFFICIAL INSTALLATION FACTS

- Use the specified 3/8-24 UNF mounting configuration.
- Maintain the ordered 1.5 m total length system length.
- Preserve Miniature ClickLoc connector; standard cable and protect all connections.
- Use the manufacturer drawing and controlled procedure for installation.

05 OFFICIAL DOCUMENTATION

[3300 XL 8 mm Proximity Transducer System System Datasheet - 141194 Rev. AM](#)

Controlled references remain in the official data sheet and manufacturer documentation. Obtain current revisions through the manufacturer media library.

AMIKON PRODUCT SUPPORT

Amikon Limited

INFO@AMIKON.CN