3300 XL 8 MM PROXIMITY TRANSDUCER SYSTEM

Product Data Sheet

330130-075-01-00

Armored proximity extension cable

CABLE LENGTH	CABLE CONSTRUCTION	CONNECTOR PROTECTOR	APPROVAL OPTION
7.5 m	**Armored standard cable**	**Not included**	**Not required**

Bently Nevada 330130-075-01-00 is a Armored proximity extension cable in the 3300 XL 8 mm proximity transducer system. The complete order code identifies 7.5 m armored standard extension cable.

01 VERIFIED TECHNICAL DATA

Cable length	7.5 m
Cable construction	Armored standard cable
Connector protector	Not included
Approval option	Not required
Insulation	FEP
Signal conductors	Triaxial
Cable impedance	75 ohm
Connector type	Miniature coaxial ClickLoc
Length tolerance	+20% / -0%
System compatibility	3300 XL 8 mm

Values follow the applicable manufacturer documents identified on page 2.

02 ADDITIONAL PRODUCT DATA

Operating temperature	-51 to +177 deg C
Armor material	FEP-coated armor

03 DOCUMENTED USE SETTINGS

Thermal Electricity and Hydroelectric Power Generation: Combined-Cycle Electricity Generation.

Petroleum Production and Natural Gas Transmission: Upstream Petroleum Production.

Metal Processing and Mineral Resource Production: Ferrous and Nonferrous Metals.

04 SYSTEM COMPATIBILITY

Integrate 330130-075-01-00 only within the compatible 3300 XL 8 mm proximity transducer system. The complete code must agree with the mating sensor chain, mounting arrangement and signal-conditioning hardware.

05 PRODUCT EVIDENCE

Bently Nevada official manufacturer document for 3300 XL 8 mm proximity transducer system

AMIKON PRODUCT SUPPORT

+86-18020776786 INFO@AMIKON.CN **AMIKONG.COM**