

SINAMICS V20

Product Data Sheet

6SL3210-5BE13-7UV0

SINAMICS V20 0.37 kW basic converter

FUNCTION	FAMILY	ORIGIN	WEIGHT
SINAMICS V20 0.37 kW basic	SINAMICS V20	Not stated	0.90 kg

Siemens 6SL3210-5BE13-7UV0 is a SINAMICS V20 0.37 kW basic converter for the SINAMICS V20. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

Drive family	SINAMICS V20
Converter type	Basic converter
Input phases	3 AC
Line voltage	380 to 480 V AC
Line frequency	47 to 63 Hz
Rated power	0.37 kW
Rated output current	1.30 A
Rated output voltage	400 V
Pulse frequency	2 kHz
Output frequency	0 to 550 Hz

Power factor	0.95
Displacement factor	0.98
Cooling method	Convection cooling
Mounting position	Wall or side by side
Protection class	IP20

- Industrial Manufacturing and Continuous Production: Discrete manufacturing and assembly production; Continuous industrial production operations
- Municipal Water and Industrial Wastewater Services: Municipal water treatment services; Industrial wastewater treatment operations
- Heating, Ventilation and Building Utility Services: Heating and chilled-water distribution services; Ventilation and indoor-air management

Match 6SL3210-5BE13-7UV0 to the installed SINAMICS V20, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

[Siemens technical document for 6SL3210-5BE13-7UV0](#)

Manufacturer document archive: 6SL3210-5BE13-7UV0.pdf

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM