

SENTRON PAC AND 3VA COMMUNICATION

Product Data Sheet

7KM9300-0AE01-0AA0

SENTRON switched Ethernet PROFINET module

FUNCTION	FAMILY	ORIGIN	WEIGHT
SENTRON switched Ethernet PROFINET	SENTRON PAC and 3VA communication	Not stated	0.09 kg

Siemens 7KM9300-0AE01-0AA0 is a SENTRON switched Ethernet PROFINET module for the SENTRON PAC and 3VA communication. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

Product designation	Switched Ethernet PROFINET expansion module
Compatible meters	SENTRON PAC3200 and PAC4200
Compatible communication units	3VA COM100 and COM800
Network protocol	PROFINET
Ethernet ports	2 RJ45 sockets
Supply method	Via host device
Galvanic isolation	500 V AC maximum
Protection class	IP20
Flammability class	UL 94 V 0
Pollution degree	2

ADDITIONAL PRODUCT DATA

Mounting method	Plug in
Operating temperature minimum	-5 °C
Operating temperature maximum	55 °C
Storage temperature minimum	-25 °C
Storage temperature maximum	70 °C

OFFICIAL APPLICATIONS

- Thermal, Hydroelectric and Renewable Power Generation: Thermal and hydroelectric power production; Renewable generation and energy integration
- Industrial Manufacturing and Continuous Production: Discrete manufacturing and assembly production; Continuous industrial production operations
- Commercial and Institutional Building Operations: Commercial property operations; Institutional facility services

SYSTEM COMPATIBILITY

Match 7KM9300-0AE01-0AA0 to the installed SENTRON PAC and 3VA communication, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

OFFICIAL SOURCES

[Siemens technical document for 7KM9300-0AE01-0AA0](#)

Manufacturer document archive: 7KM9300-0AE01-0AA0.pdf

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM