

SIMATIC ET 200B

Product Data Sheet

6ES7193-0CB30-0XA0

ET 200B TB4 DC terminal block

FUNCTION ET 200B TB4 DC terminal	FAMILY SIMATIC ET 200B	ORIGIN Not stated	WEIGHT 0.80 kg
--	----------------------------------	-----------------------------	--------------------------

Siemens 6ES7193-0CB30-0XA0 is a ET 200B TB4 DC terminal block for the SIMATIC ET 200B. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

System family	SIMATIC ET 200B
Terminal block designation	TB4/DC
Supported submodules	Digital electronic submodules
Wiring arrangement	3 wire
Terminal technology	Spring loaded terminals
Rated supply	24 V DC
Permitted supply minimum	18.5 V DC
Permitted supply maximum	30 V DC
Typical current consumption	100 mA
Maximum current consumption	200 mA

ADDITIONAL PRODUCT DATA

PROFIBUS isolation	Electronics isolated from PROFIBUS DP
Protection class	IP20
Operating temperature minimum	0 °C
Operating temperature maximum	60 °C
Product status	Spare part

OFFICIAL APPLICATIONS

- Industrial Manufacturing and Continuous Production: Discrete manufacturing and assembly production; Continuous industrial production operations
- Thermal, Hydroelectric and Renewable Power Generation: Thermal and hydroelectric power production; Renewable generation and energy integration
- Municipal Water and Industrial Wastewater Services: Municipal water treatment services; Industrial wastewater treatment operations

SYSTEM COMPATIBILITY

Match 6ES7193-0CB30-0XA0 to the installed SIMATIC ET 200B, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

OFFICIAL SOURCES

[Siemens technical document for 6ES7193-0CB30-0XA0](#)

Manufacturer document archive: 6ES7193-0CB30-0XA0.pdf

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM