

MANUFACTURER DOCUMENT PACKAGE

Manufacturer's Manual

Amikon cover with selected official Siemens pages

SIMATIC NET PROFIBUS PA

6GK1905-0AA00

PROFIBUS PA SPLIT CONNECT TAP

OFFICIAL SOURCES

Siemens official PDF. Selected pages retain their original content, color and aspect ratio.

Product-type designation

SpliT Connect Tap



PROFIBUS PA SPLITCONNECT TAP,
FOR ASSEMBLING OF PROFIBUS PA SEGMENTS AND
CONNECTION OF PA FIELD DEVICES,
INSULATION DISPLACEMENT TERMINAL,
IP67 PACK. UNIT: 10 PIECES = 1 PACK

Interfaces

Number of electrical connections

- for PROFIBUS cables

3

Design of the electrical connection

- for PROFIBUS cables

integrated insulation displacement contacts

Mechanical data

Material / of the enclosure

PBT (polybutyleneterephthalate)

Width

84 mm

Height

54 mm

Depth

49 mm

Net weight

170 g

Type of mounting

- 35 mm DIN rail mounting
- wall mounting

Yes

Yes

Permitted ambient conditions

Ambient temperature

- during operating
- during storage
- during transport

-40 ... +85 °C

-40 ... +85 °C

-40 ... +85 °C

Protection class IP

IP67

Standards, specifications, approvals

Verification of suitability

- UL-registration

Yes

letzte Änderung:

Feb 4, 2013