MANUFACTURER DOCUMENT PACKAGE

Manufacturer's Manual

Reference package for procurement and maintenance review

SIEMENS

6ES7132-6BD20-0BA0

ET 200SP FOUR-CHANNEL DIGITAL OUTPUT MODULE

Used with the applicable SIMATIC ET 200SP configuration.

REFERENCE PACKAGE

OFFICIAL DOCUMENT

Complete official manufacturer PDF follows this cover.

Source: Siemens official technical documentation for 6ES7132-6BD20-0BA0

SIEMENS

Data sheet 6ES7132-6BD20-0BA0



SIMATIC ET 200SP, digital output module, DQ 4x 24VDC/2A Standard, suitable for BU type A0, Color code CC02, Module diagnostics

General information	
Product type designation	DQ 4x24 V DC/2 A ST
HW functional status	From FS08
Firmware version	V1.1
● FW update possible	Yes
usable BaseUnits	BU type A0
Color code for module-specific color identification plate	CC02
Product function	
● I&M data	Yes; I&M0 to I&M3
● Isochronous mode	No
Engineering with	
● STEP 7 TIA Portal configurable/integrated from version	V11 SP2 / V13
● STEP 7 configurable/integrated from version	V5.5 SP3 / -
● PCS 7 configurable/integrated from version	V8.1 SP1
● PROFIBUS from GSD version/GSD revision	GSD Revision 5
● PROFINET from GSD version/GSD revision	GSDML V2.3
Operating mode	
● DQ	Yes
● DQ with energy-saving function	No
● PWM	No
● Oversampling	No
● MSO	No
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption, max.	60 mA; without load
output voltage / header	
Rated value (DC)	24 V
Power loss	
Power loss, typ.	1 W
Address area	
Address space per module	
● Address space per module, max.	1 byte; + 1 byte for QI information
Hardware configuration	
Automatic encoding	
● Mechanical coding element	Yes
● Type of mechanical coding element	Type A

Subject to change without notice
© Copyright Siemens

Selection of BaseUnit for connection variants	
● 1-wire connection	BU type A0
● 2-wire connection	BU type A0
● 3-wire connection	BU type A0 with AUX terminals or potential distributor module
● 4-wire connection	BU type A0 + Potential distributor module
Digital outputs	
Type of digital output	Source output (PNP, current-sourcing)
Number of digital outputs	4
Current-sinking	No
Current-sourcing	Yes
Digital outputs, parameterizable	Yes
Short-circuit protection	Yes
● Response threshold, typ.	2.8 to 5.2 A
Limitation of inductive shutdown voltage to	Typ. L+ (-50 V)
Controlling a digital input	Yes
Switching capacity of the outputs	
● with resistive load, max.	2 A
● on lamp load, max.	10 W
Load resistance range	
● lower limit	12 Ω
● upper limit	3 400 Ω
Output current	
● for signal "1" rated value	2 A
● for signal "0" residual current, max.	0.1 mA
Output delay with resistive load	
● "0" to "1", typ.	50 µs
● "0" to "1", max.	50 µs
● "1" to "0", typ.	100 µs
● "1" to "0", max.	100 µs
Parallel switching of two outputs	
● for uprating	No
● for redundant control of a load	Yes
Switching frequency	
● with resistive load, max.	100 Hz
● with inductive load, max.	2 Hz
● on lamp load, max.	10 Hz
Total current of the outputs	
● Current per channel, max.	2 A
● Current per module, max.	8 A
Total current of the outputs (per module)	
horizontal installation	
— up to 40 °C, max.	8 A
— up to 50 °C, max.	6 A
— up to 60 °C, max.	4 A
vertical installation	
— up to 30 °C, max.	8 A
— up to 40 °C, max.	6 A
— up to 50 °C, max.	4 A
— up to 60 °C, max.	4 A
Cable length	
● shielded, max.	1 000 m
● unshielded, max.	600 m
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Substitute values connectable	Yes
Alarms	
● Diagnostic alarm	Yes
Diagnoses	
● Monitoring the supply voltage	Yes
● Wire-break	Yes; Module-wise
● Short-circuit	Yes; Module-wise

Subject to change without notice
© Copyright Siemens

● Group error	Yes
Diagnostics indication LED	
● Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
● Channel status display	Yes; green LED
● for channel diagnostics	No
● for module diagnostics	Yes; green/red DIAG LED
Potential separation	
Potential separation channels	
● between the channels	No
● between the channels and backplane bus	Yes
● between the channels and the power supply of the electronics	No
Isolation	
Isolation tested with	707 V DC (type test)
Standards, approvals, certificates	
Suitable for safety functions	No
Suitable for safety-related tripping of standard modules	Yes; see FAQ Entry ID: 39198632
Highest safety class achievable in safety mode	
● Performance level according to ISO 13849-1	PL d
● SIL acc. to IEC 61508	SIL 2
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	-30 °C; < 0 °C as of FS08
● horizontal installation, max.	60 °C
● vertical installation, min.	-30 °C; < 0 °C as of FS08
● vertical installation, max.	50 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
Dimensions	
Width	15 mm
Height	73 mm
Depth	58 mm
Weights	
Weight, approx.	30 g

last modified: 8/16/2023

Subject to change without notice
© Copyright Siemens