SIMATIC S7-1500

Product Data Sheet

6EP1332-4BA00

PM1507 24 V 3 A power supply

FUNCTION	FAMILY	ORIGIN	WEIGHT
PM1507 24 V 3 A	**SIMATIC S7-1500**	**Germany**	**0.60 kg**

Siemens 6EP1332-4BA00 is a PM1507 24 V 3 A power supply for the SIMATIC S7-1500. The values below are limited to the exact documented article.

01 VERIFIED TECHNICAL DATA

Input protection	Internal input fuse and electronic output protection
Input selection	120 or 230 V AC
Input range	85 to 264 V AC
Line frequency	45 to 65 Hz
Rated output voltage	24 V DC
Rated output current	3 A
Rated output power	72 W
Mains buffering	At least 20 ms
Short term overload	12 A for 70 ms
Parallel units	Maximum 2

02 ADDITIONAL PRODUCT DATA

Typical efficiency	87 percent
Power loss at rated load	11 W
Output tolerance	Plus or minus 3 percent
Mounting method	S7 1500 profile rail
Protection class	IP20

03 OFFICIAL APPLICATIONS

- Industrial Manufacturing and Continuous Production: Discrete manufacturing and assembly production; Continuous industrial production operations
- Municipal Water and Industrial Wastewater Services: Municipal water treatment services; Industrial wastewater treatment operations
- Thermal, Hydroelectric and Renewable Power Generation: Thermal and hydroelectric power production; Renewable generation and energy integration

04 SYSTEM COMPATIBILITY

Match 6EP1332-4BA00 to the installed SIMATIC S7-1500, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

05 OFFICIAL SOURCES

Siemens official technical documentation for 6EP1332-4BA00

Applicable manufacturer documentation retained in Manuals & support

AMIKON PRODUCT SUPPORT

+86-18020776786 INFO@AMIKON.CN **AMIKONG.COM**