

LOGO 0BA4

Product Data Sheet

6ED1052-2MD00-0BA4

LOGO 12 24 RCo basic module

FUNCTION LOGO 12 24 RCo basic	FAMILY LOGO 0BA4	ORIGIN Germany	WEIGHT 0.19 kg
---	----------------------------	--------------------------	--------------------------

Siemens 6ED1052-2MD00-0BA4 is a LOGO 12 24 RCo basic module for the LOGO 0BA4. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

Controller interface	LOGO basic module expansion connector
Controller generation	0BA4
Display	Without display
Supply voltage	12 or 24 V DC
Digital inputs	8
Analog capable inputs	2 inputs at 0 to 10 V
Relay outputs	4
Program capacity	130 function blocks
Relay contact rating	10 A resistive load
Logic functions	Boolean logic, timers, counters and analog processing

ADDITIONAL PRODUCT DATA

Analog input range	0 to 10 V
Expansion interface	LOGO expansion bus
Clock function	Integrated real time clock
Programming interface	LOGO PC cable interface
Mounting method	35 mm DIN rail

OFFICIAL APPLICATIONS

- Industrial Manufacturing and Continuous Production: Discrete manufacturing and assembly production; Continuous industrial production operations
- Municipal Water and Industrial Wastewater Services: Municipal water treatment services; Industrial wastewater treatment operations
- Thermal, Hydroelectric and Renewable Power Generation: Thermal and hydroelectric power production; Renewable generation and energy integration

SYSTEM COMPATIBILITY

Match 6ED1052-2MD00-0BA4 to the installed LOGO 0BA4, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

OFFICIAL SOURCES

[Siemens official technical documentation for 6ED1052-2MD00-0BA4](#)

Applicable manufacturer documentation retained in Manuals & support

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM