SIMATIC S7-200 SMART

Product Data Sheet

6ES7288-1CR40-0AA1

CPU CR40 AC/DC/Relay Controller

FUNCTION	FAMILY	ORIGIN	WEIGHT
CPU CR40 AC/DC/Relay Controller	**SIMATIC S7-200 SMART**	**China**	**0.44 kg**

Siemens 6ES7288-1CR40-0AA1 is a CPU CR40 AC/DC/Relay Controller for the SIMATIC S7-200 SMART. The values below are limited to the exact documented article.

01 VERIFIED TECHNICAL DATA

AC supply range	85 to 264 V AC, 47 to 63 Hz
Onboard digital inputs	24, nominal 24 V DC
Onboard digital outputs	16
Output technology	Relay, dry contact
Program memory	12 KB
Ethernet interface	Not available
Serial interface	1 x RS485
Expansion modules	Not supported
Signal-board expansion	Not supported
Sensor-power output	24 V DC, 300 mA maximum

02 ADDITIONAL PRODUCT DATA

Output current per point	2 A maximum; observe common-group and load-type limits
Memory card	Not supported
User data memory	8 KB
PROFINET IO roles	Neither controller nor I-Device
Product type designation	CPU CR40 AC/DC/Relay

03 OFFICIAL APPLICATIONS

- Control and monitoring systems: Model specific integration and maintenance
- Plant production equipment: Documented signal and communication functions
- Installed base maintenance: Exact article replacement and commissioning

04 SYSTEM COMPATIBILITY

Match 6ES7288-1CR40-0AA1 to the installed SIMATIC S7-200 SMART, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

05 OFFICIAL SOURCES

Siemens official technical documentation for 6ES7288-1CR40-0AA1

C:\Users\Administrator\Desktop\AMIKONG■■■\6ES7288-1CR40-0AA1.pdf

AMIKON PRODUCT SUPPORT

+86-18020776786 INFO@AMIKON.CN **AMIKONG.COM**