MANUFACTURER DOCUMENT PACKAGE

Manufacturer's Manual

Reference package for procurement and maintenance review

SIEMENS

6ES7288-3AE08-0AA0

SM AI08 ANALOG INPUT MODULE

Used with the applicable SIMATIC S7-200 SMART configuration.

REFERENCE PACKAGE

OFFICIAL DOCUMENT

Selected official manufacturer pages follow this cover.

Source: Siemens technical documentation for 6ES7288-3AE08-0AA0

SIEMENS

Data sheet 6ES7288-3AE08-0AA0

	SIMATIC S7-200 SMART, Analog input SM AI08, 8 AI, 0...10V, 0...5V, +/-5 V, +/-2.5 V or 0/4-20 mA; 11 bit + sign (12 bit ADC)
General information	
Product type designation	SM AI08, AI 8x12 bit
CiR - Configuration in RUN	
Reparameterization possible in RUN	No
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V; -15 / +20 %
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption, typ.	60 mA
Current consumption, max.	80 mA
from backplane bus 5 V DC, typ.	61 mA
from backplane bus 5 V DC, max.	80 mA
Power loss	
Power loss, typ.	2 W
Analog inputs	
Number of analog inputs	8
Input ranges	
● Voltage	Yes
● Current	Yes
● Thermocouple	No
● Resistance thermometer	No
● Resistance	No
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
● Resolution with overrange (bit including sign), max.	12 bit
Dimensions	
Width	45 mm
Height	100 mm
Depth	81 mm
Weights	
Weight, approx.	186 g

last modified: 3/12/2024

Subject to change without notice
© Copyright Siemens