MANUFACTURER DOCUMENT PACKAGE

Manufacturer's Manual

Reference package for procurement and maintenance review

SIEMENS

6ES7288-3AM06-0AA0

SM AM06 ANALOG INPUT/OUTPUT MODULE

Used with the applicable SIMATIC S7-200 SMART configuration.

REFERENCE PACKAGE

OFFICIAL DOCUMENT

Selected official manufacturer pages follow this cover.

Source: Siemens technical documentation for 6ES7288-3AM06-0AA0

SIEMENS

Data sheet 6ES7288-3AM06-0AA0

SIMATIC S7-200 SMART, analog I/O SM AM06, 4 AI/2 AO, 0..10 V, 0..5 V, 0/4..20mA, +/-5 V, +/-2.5 V, 12 bit resolution or 4...20 mA, +/-10 V 11 bit resolution



General information	
Product type designation	SM AM06, AI 4x12 bit, AQ 2x11 bit
CiR – Configuration in RUN	
Reparameterization possible in RUN	No
Supply voltage	
Rated value (DC)	
• 24 V DC	Yes; -15 / +20 %
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption, typ.	60 mA
from backplane bus 5 V DC, typ.	80 mA
Power loss	
Power loss, typ.	2 W
Analog inputs	
Number of analog inputs	4
Input ranges	

Subject to change without notice
© Copyright Siemens

• Voltage	Yes; ±10V, ±5V, ±2.5V
• Current	Yes; 0 to 20 mA
• Thermocouple	No
• Resistance thermometer	No
• Resistance	No
Input ranges (rated values), voltages	
• -10 V to +10 V	Yes
— Input resistance (-10 V to +10 V)	9 MΩ
• -2.5 V to +2.5 V	Yes
— Input resistance (-2.5 V to +2.5 V)	9 MΩ
• -5 V to +5 V	Yes
— Input resistance (-5 V to +5 V)	9 MΩ
Input ranges (rated values), currents	
• 0 to 20 mA	Yes
— Input resistance (0 to 20 mA)	250 Ω
Analog outputs	
Number of analog outputs	2; Current or voltage
Output ranges, voltage	
• -10 V to +10 V	Yes
Output ranges, current	
• 0 to 20 mA	Yes
Load impedance (in rated range of output)	
• with voltage outputs, min.	1 kΩ
• with current outputs, max.	500 Ω
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
• Resolution (incl. overrange)	voltage mode: 11 bit + sign bit, current mode: 11 bit
• Resolution with overrange (bit including sign), max.	12 bit
• Interference voltage suppression for interference frequency f1 in Hz	10 / 50 / 60 / 400 Hz
Smoothing of measured values	
• parameterizable	Yes; In 4 stages: 1x, 4x, 16x, 32x cycle time
• Step: None	Yes; 1x
• Step: low	Yes; 4x
• Step: Medium	Yes; 16x
• Step: High	Yes; 32x
Analog value generation for the outputs	
Integration and conversion time/resolution per channel	
• Resolution (incl. overrange)	voltage mode: 11 bit + sign bit, current mode: 11 bit

Subject to change without notice
© Copyright Siemens

• Resolution in isochronous mode (including overrange)	voltage mode: 10 bit + sign bit, current mode: 10 bit
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Diagnostic messages	
• Monitoring the supply voltage	Yes
• Wire-break	Yes
• Short-circuit	Yes
Diagnostics indication LED	
• for status of the inputs	Yes
• for status of the outputs	Yes
Degree and class of protection	
Degree of protection acc. to EN 60529	
• IP20	Yes
Standards, approvals, certificates	
CE mark	Yes
Dimensions	
Width	45 mm
Height	100 mm
Depth	81 mm
Weights	
Weight, approx.	173.4 g

last modified: 04/09/2020

Subject to change without notice
© Copyright Siemens