MOLEX APPLICOM S7/MPI

Product Data Sheet

APP-PS7-PCU-C PCU1500S7

PCU1500S7 PROFIBUS interface card

FUNCTION	FAMILY	ORIGIN	WEIGHT
PCU1500S7 PROFIBUS interface card	**Molex applicom S7/MPI**	**United States**	**0.14 kg**

SST APP-PS7-PCU-C PCU1500S7 is a PCI Universal PROFIBUS communication card for the Molex applicom S7/MPI. The values below are limited to the exact documented article.

01 VERIFIED TECHNICAL DATA

Order number	112011-0006
Model	APP-PS7-PCU-C / PCU1500S7
Fieldbus interface	One PROFIBUS DB9 female port
Galvanic isolation	500 V
PROFIBUS speed	9.6 kbit/s to 1.5 Mbit/s
Host bus	PCI Universal 3.3 V and 5 V
Processor	AMD SC520
Working memory	16 MB SDRAM
Flash memory	4 MB
Power consumption	5.5 W

Technical values are limited to the exact manufacturer record and applicable official manual.

02 ADDITIONAL PRODUCT DATA

Supported master modes	S7/MPI, PPI and PPI+
FDL service	Send and receive
Installation	Plug-and-play PCI card
Connector	Shielded nine-pin Sub-D
Compliance	CE and RoHS

03 OFFICIAL APPLICATIONS

- Industrial Manufacturing
- Automotive Manufacturing
- Material Handling

04 SYSTEM COMPATIBILITY

Match APP-PS7-PCU-C PCU1500S7 to the installed Molex applicom S7/MPI, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

05 OFFICIAL SOURCES

SST technical documentation for APP-PS7-PCU-C PCU1500S7

https://www.molex.com/en-us/products/part-detail/1120110006

AMIKON PRODUCT SUPPORT

+86-18020776786 INFO@AMIKON.CN **AMIKONG.COM**