SENTRON PAC3200

Product Data Sheet

7KM2111-1BA00-3AA0

SENTRON PAC3200 power monitoring device

FUNCTION	FAMILY	ORIGIN	WEIGHT
SENTRON PAC3200 power monitoring d	**SENTRON PAC3200**	**Germany**	**0.451 kg**

Siemens 7KM2111-1BA00-3AA0 is a panel-mounted power monitoring device for the SENTRON PAC3200. The values below are limited to the exact documented article.

01 VERIFIED TECHNICAL DATA

Display	128 × 96 pixel LCD
Panel format	96 × 96 mm
Panel cutout	92 × 92 mm
Auxiliary supply	22 to 65 V DC
Maximum phase voltage	500 V AC
Maximum phase-to-neutral voltage	289 V AC
Frequency range	45 to 65 Hz
Current transformer input	1 A or 5 A selectable
Measurement method	True RMS
Communication	10 Mbit/s Ethernet

02 ADDITIONAL PRODUCT DATA

Protocols	Modbus TCP and SEAbus TCP
Front protection	IP65
Rear protection	IP20
Consumption	8 VA maximum with expansion
Short-time current withstand	100 A for 1 second

03 OFFICIAL APPLICATIONS

- Industrial Manufacturing
- Commercial Buildings
- Power Generation

04 SYSTEM COMPATIBILITY

Match 7KM2111-1BA00-3AA0 to the installed SENTRON PAC3200, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

05 OFFICIAL SOURCES

Siemens technical documentation for 7KM2111-1BA00-3AA0

https://support.industry.siemens.com/

AMIKON PRODUCT SUPPORT

+86-18020776786 INFO@AMIKON.CN **AMIKONG.COM**