MANUFACTURER DOCUMENT PACKAGE

Manufacturer's Manual

Reference package for procurement and maintenance review

SIEMENS

6ES7216-2AD23-0XB0

CPU 226 DC/DC/DC

Used with the applicable S7-200 configuration.

REFERENCE PACKAGE

OFFICIAL DOCUMENT

Selected official manufacturer pages follow this cover.

Source: Siemens technical documentation for 6ES7216-2AD23-0XB0

SIEMENS

Data sheet 6ES7216-2AD23-0XB0

SIMATIC S7-200, CPU 226 COMPACT UNIT, DC POWER SUPPLY 24 DI DC/16 DO DC, 16/24 KB CODE/10 KB DATA, 2 PPI/FREEPORT PORTS



Figure similar

Supply voltage	
Rated value (DC)	
• 24 V DC	Yes
Load voltage L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	20.4 V
• permissible range, upper limit (DC)	28.8 V
Input current	
Inrush current, max.	10 A; at 28.8 V
from supply voltage L+, max.	1 050 mA; 150 mA to 1 050 mA output current for expansion modules (5 V DC) 1 000 mA
Encoder supply	
24 V encoder supply	
• 24 V	Yes; permissible range: 15.4 to 28.8 V
• Short-circuit protection	Yes; electronic at 400 mA
• Output current, max.	400 mA

Subject to change without notice
© Copyright Siemens

Memory	
Number of memory modules (optional)	1; pluggable memory module, content identical with integral EEPROM; can additionally store recipes, data logs and other files
Work memory	
• integrated (for program)	24 kbyte; 16 KB with active run-time edit
• integrated (for data)	10 kbyte
Backup	
• present	Yes; Program: Entire program maintenance-free on integral EEPROM, programmable via CPU; data: Entire DB 1 loaded from PG/PC maintenance-free on integral EEPROM, current values of DB 1 in RAM, retentive memory bits, timers, counters, etc. maintenance-free via high-performance capacitor; optional battery for long-term buffering
Battery	
Backup battery	
• Backup time, max.	100 h; (min. 70 h at 40 °C); 200 days (typ.) with optional battery module
CPU processing times	
for bit operations, max.	0.22 µs
Counters, timers and their retentivity	
S7 counter	
• Number	256
of which retentive with battery	
— can be set	Yes; via high-performance capacitor or battery
— lower limit	1
— upper limit	256
Counting range	
— lower limit	0
— upper limit	32 767
S7 times	
• Number	256
of which retentive with battery	
— adjustable	Yes; via high-performance capacitor or battery
— upper limit	64
Time range	
— lower limit	1 ms
— upper limit	54 min; 4 timers: 1 ms to 30 s; 16 timers: 10 ms to 5 min; 236 timers: 100 ms to 54 min
Data areas and their retentivity	
Flag	
• Number, max.	32 byte
• Retentivity available	Yes; M 0.0 to M 31.7

Subject to change without notice
© Copyright Siemens

• of which retentive with battery	0 to 255, via high-performance capacitor or battery, adjustable
• of which retentive without battery	0 to 112 in EEPROM, adjustable
Hardware configuration	
Number of expansion units, max.	7; Only expansion modules of the S7-22x series can be used. Due to the limited output current, the use of expansion modules may be limited.
connectable programming devices/PCs	SIMATIC PG/PC, standard PC
Expansion modules	
• Analog inputs/outputs, max.	35; max. 28 inputs and 7 outputs (EM) or max. 0 inputs and 14 outputs (EM)
• Digital inputs/outputs, max.	148; max. 128 inputs and 120 outputs (CPU+EM)
• AS-Interface inputs/outputs, max.	62; AS-Interface A/B slaves (CP 243-2)
Digital inputs	
Number of digital inputs	24
Source/sink input	Yes; optionally, per group
Input voltage	
• Rated value (DC)	24 V
• for signal "0"	0 to 5 V
• for signal "1"	min. 15 V
Input current	
• for signal "1", typ.	2.5 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes; all
— at "0" to "1", min.	0.2 ms
— at "0" to "1", max.	12.8 ms
for interrupt inputs	
— parameterizable	Yes; I 0.0 to I 0.3
for counter/technological functions	
— parameterizable	Yes; (E 0.0 to E 1.5) 30 kHz
Cable length	
• shielded, max.	500 m; Standard input: 500 m, high-speed counters: 50 m
• unshielded, max.	300 m; not for high-speed signals
Digital outputs	
Number of digital outputs	16; Transistor
Short-circuit protection	No; to be provided externally
Limitation of inductive shutdown voltage to	1 W
Switching capacity of the outputs	
• with resistive load, max.	0.75 A
• on lamp load, max.	5 W
Output voltage	

Subject to change without notice
© Copyright Siemens