24701 PROXIMITY PROBE HOUSING ASSEMBLY

Product Data Sheet

24701-28-10-25-080-03-02

External proximity probe housing

PROBE OPTION	PROBE CABLE LENGTH	STANDOFF ADAPTER	PROBE PENETRATION
3300 XL 8 mm with multiple approvals	**1.0 m**	**2.5 in**	**8.0 in**

Bently Nevada 24701-28-10-25-080-03-02 is a External proximity probe housing in the 24701 proximity probe housing assembly. The complete order code identifies 1.0 m probe lead, 2.5-inch standoff and 8.0-inch penetration.

01 VERIFIED TECHNICAL DATA

Probe option	3300 XL 8 mm with multiple approvals
Probe cable length	1.0 m
Standoff adapter	2.5 in
Probe penetration	8.0 in
Fittings configuration	Plug, reducer and cable seal grip
Mounting thread	3/4-14 NPT
Housing material	303 stainless steel
Sleeve material	304 stainless steel
Penetration adjustment	+/-13 mm
Enclosure rating	CSA Type 4

Values follow the applicable manufacturer documents identified on page 2.

02 ADDITIONAL PRODUCT DATA

Measurement principle	Eddy-current proximity sensing
Linear range	0.25 to 2.30 mm
Nominal scale factor	7.87 V/mm
Frequency response	0 to 10 kHz
Calibration target	AISI 4140 steel

03 DOCUMENTED USE SETTINGS

External Probe Access and Mechanical Protection: Protected proximity probe access at turbine bearing housings.

Compression and Pumping Machinery Condition Monitoring: Pipeline compressor bearing vibration across transmission stations.

Rolling Mill and Mineral Processing Machinery Monitoring: Rolling mill drive vibration across metal processing operations.

04 SYSTEM COMPATIBILITY

Integrate 24701-28-10-25-080-03-02 only within the compatible 24701 proximity probe housing assembly. The complete code must agree with the mating sensor chain, mounting arrangement and signal-conditioning hardware.

05 PRODUCT EVIDENCE

Bently Nevada official manufacturer document for 24701 proximity probe housing assembly

AMIKON PRODUCT SUPPORT

+86-18020776786 INFO@AMIKON.CN **AMIKONG.COM**