MANUFACTURER DOCUMENT PACKAGE

Manufacturer's Manual

Amikon cover with selected official Siemens pages

SIMATIC ET 200SP HA

6DL1193-6BH00-0RM0

BASE UNIT

OFFICIAL SOURCES

Siemens official product documentation. Selected pages retain their original content, color and aspect ratio.

SIEMENS

Data sheet 6DL1193-6BH00-0RM0

Siemens EcoTech

SIMATIC ET 200SP HA, Carrier module in redundant carrier for holding 2 interface modules of the ET 200SP HA incl. server module



Figure similar

General information	
Product type designation	Carrier module IM redundant
Product function	
● I&M data	Yes; Asset data
Supply voltage	
Rated value (DC)	24 V
Hardware configuration	
Slots	
● Number of slots	2
Potential separation	
between backplane bus and supply voltage	Yes
Isolation	
Isolation tested with	1 500 V DC/1 min, type test
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	-40 °C
● horizontal installation, max.	70 °C
● vertical installation, min.	-40 °C
● vertical installation, max.	60 °C
Dimensions	
Width	100 mm
Height	204 mm
Depth	29 mm; measured without power plug
Weights	
Weight, approx.	224 g
Classifications	

	Version	Classification
eClass	14	27-24-26-07
eClass	12	27-24-26-07
eClass	9.1	27-24-26-07
eClass	9	27-24-26-07
eClass	8	27-24-26-07
eClass	7.1	27-24-26-07

Subject to change without notice
© Copyright Siemens

eClass	6	27-24-26-07
ETIM	10	EC001603
ETIM	9	EC001603
ETIM	8	EC001603
ETIM	7	EC001603

Approvals / Certificates

General Product Approval



Miscellaneous



China RoHS





General Product Approval





For use in hazardous locations



Declaration of Conformity





For use in hazardous locations





Miscellaneous

Maritime application







Maritime application



NK / Nippon Kaiji Kyokai



CCS (China Classification Society)

Environment





last modified: 10/23/2025

Subject to change without notice
© Copyright Siemens