MANUFACTURER DOCUMENT PACKAGE

Manufacturer's Manual

Reference package for procurement and maintenance review

SIEMENS

6ES7901-3DB30-0XA0

USB/PPI MULTI-MASTER CABLE

Used with the applicable SIMATIC S7-200 configuration.

REFERENCE PACKAGE

OFFICIAL DOCUMENT

Selected official manufacturer pages follow this cover.

Source: Siemens product data sheet, 6ES7901-3DB30-0XA0

SIEMENS

Data sheet 6ES7901-3DB30-0XA0

SIMATIC S7-200, USB/PPI cable MM MULTIMASTER, for connection of S7-200 to USB PC interface, no Freeport support



General information	
Product type designation	USB/PPI multi-master
Supply voltage	
Design of the power supply	From USB interface
Interfaces	
Point-to-point connection	
• Transmission rate, max.	187.5 kbit/s; 9.6 / 19.2 / 187.5 kbit/s; setting: not necessary
Protocols	
PPI	Yes; 10/11 bit
Interrupts/diagnostics/status information	
LED status display	Tx (green): USB send display; Rx (green): USB receive display; PPI (green): RS-485 send display
Potential separation	
Potential separation exists	Yes
Weights	
Weight, approx.	300 g

Subject to change without notice
© Copyright Siemens