SIRIUS 3RW30

Product Data Sheet

3RW3014-1BB04

6.5 A Soft Starter

FRAME SIZE	MAIN CIRCUIT VOLTAGE	CONTROL SUPPLY	RATED CURRENT AT 40 °C
S00	**200–480 V AC**	**24 V AC/DC**	**6.5 A**

Siemens 3RW3014-1BB04 is the 6.5 A Soft Starter for SIRIUS 3RW30. This SIRIUS 3RW30 soft starter provides ramped motor starting and an integrated bypass in the S00 frame.

01 TECHNICAL DATA

Frame size	S00
Main circuit voltage	200–480 V AC
Control supply	24 V AC/DC
Rated current at 40 °C	6.5 A
Rated current at 50 °C	6 A
Rated current at 60 °C	5.5 A
Motor power at 400 V and 40 °C	3 kW
Rated frequency	50–60 Hz
Integrated bypass	Yes
Adjustable current limitation	No

02 ADDITIONAL PRODUCT DATA

Motor overload protection	Not integrated
Terminals	Screw

03 PRODUCT FUNCTION

Frame size is specified as S00. The published data also lists 200–480 V AC for main circuit voltage and 24 V AC/DC for control supply.

04 SYSTEM COMPATIBILITY

Check the 24 V AC/DC control feed and size the starter for motor current at the expected ambient temperature. Compare the project settings with the corresponding product ratings.

05 REFERENCE

Siemens product data sheet, 3RW3014-1BB04

AMIKON PRODUCT SUPPORT
+86-18020776786 INFO@AMIKON.CN AMIKONG.COM