3300 XL NSV PROXIMITY TRANSDUCER

Product Data Sheet

330901-00-36-10-11-05

3300 XL NSv Proximity Probe

MOUNTING THREAD	CASE LENGTH	UNTHREADED LENGTH	INTEGRAL LEAD LENGTH
1/4-28 UNF	**3.6 in**	**0.0 in**	**1 m**

Bently Nevada 330901-00-36-10-11-05 is a 3300 XL NSv proximity probe for noncontact measurement of shaft vibration and position. Its 1/4-28 UNF threaded case supports an adjustable mounting position, and the unarmored integral lead connects the probe to a compatible extension cable and Proximitor sensor.

01 TECHNICAL DATA

Mounting thread	1/4-28 UNF
Case length	3.6 in
Unthreaded length	0.0 in
Integral lead length	1 m
Cable armor	Unarmored
Connector configuration	FluidLoc ClickLoc
Connector protector	Included
Approval selection	Multiple approvals option
Probe tip material	Polyphenylene sulfide (PPS)
Probe cable impedance	75 ohms

02 ADDITIONAL PRODUCT DATA

The case is 3.6 in long with 0.0 in of unthreaded length. This configuration has a 1 m integral lead with a FluidLoc ClickLoc connector. The connector protector is included. The probe tip uses polyphenylene sulfide and the lead uses 75-ohm coaxial cable.

03 PRODUCT FUNCTION

The case is 3.6 in long with 0.0 in of unthreaded length. This configuration has a 1 m integral lead with a FluidLoc ClickLoc connector. The connector protector is included. The probe tip uses polyphenylene sulfide and the lead uses 75-ohm coaxial cable.

04 SYSTEM COMPATIBILITY

Match the installed probe, extension cable and sensor to the approved system length and configuration.

05 REFERENCE

Bently Nevada 3300 XL NSv Proximity Transducer System Datasheet 147385

AMIKON PRODUCT SUPPORT

+86-18020776786 INFO@AMIKON.CN **AMIKONG.COM**