MANUFACTURER DOCUMENT PACKAGE

Manufacturer's Manual

Reference package for procurement and maintenance review

SIEMENS

6AV2181-5AF20-0AX0

TWENTY-METRE MOBILE PANEL CONNECTING CABLE

Used with the applicable SIMATIC HMI KTPx00(F) Mobile configuration.

REFERENCE PACKAGE

OFFICIAL DOCUMENT

Selected official manufacturer pages follow this cover.

Source: Siemens 6AV2181-5AF20-0AX0 manufacturer technical data; applicable specification pages.

SIEMENS

Data sheet 6AV2181-5AF20-0AX0



Figure similar

SIMATIC HMI connecting cable for KTPX00(F) Mobile, Length 20 m

General information	
Product type designation	Connecting cable
Standards, approvals, certificates	
CE mark	Yes
cULus	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
Suitable for safety functions	Yes
Ambient conditions	
Ambient temperature during operation	
● min.	0 °C
● max.	55 °C
Ambient temperature during storage/transportation	
● min.	-20 °C
● max.	60 °C
Cables	
Cable length	20 m
Maximum tensile load	300 N
Color of cable sheath	
● green	Yes
Scope of supply	
Delivery quantity in pieces	1
Other	
Merchandise	Yes
Manufacturer name	On request

last modified: 4/16/2021

Subject to change without notice
© Copyright Siemens