3300 XL NSV

Product Data Sheet

330903-00-07-10-01-CN

Unarmored proximity sensing probe

CASE THREAD	UNTHREADED SECTION	CASE LENGTH SELECTION	TOTAL PROBE LEAD
M8 x 1	**0 mm**	**70 mm**	**1.0 m**

Bently Nevada 330903-00-07-10-01-CN is a 3300 XL NSv proximity probe with a M8 x 1 threaded case. It senses the distance to a conductive target without contact and passes its signal through the probe lead to the matched Proximitor electronics.

01 TECHNICAL DATA

Case thread	M8 x 1
Unthreaded section	0 mm
Case length selection	70 mm
Total probe lead	1.0 m
Lead armor	Without armor
Connector protector	Connector protector fitted
Cable impedance	75 ohm
Cable insulation	FEP
Probe tip construction	PPS
Case metal	AISI 304 stainless steel

Bently Nevada 3300 XL NSv Datasheet 147385 Rev. R, applicable specification, ordering and dimensional sections.

02 ADDITIONAL PRODUCT DATA

Coaxial connector	Miniature ClickLoc
Probe resistance	4.2 +/- 0.5 ohm
Matched-chain linear range	1.5 mm
Nominal matched-chain scale	7.87 V/mm
Matched calibration target	AISI 4140 steel

03 PRODUCT FUNCTION

This configuration has a 0 mm unthreaded section, a 70 mm case-length selection and a 1.0 m total lead. The lead construction is without armor, with a miniature ClickLoc connector and connector protector fitted. The CN suffix is preserved as part of the requested identity; no unverified regional approval rating is assigned to it.

04 SYSTEM COMPATIBILITY

The specified matched chain has a 0.25 to 1.75 mm linear operating span and a nominal 7.87 V/mm scale factor on the documented AISI 4140 steel target. Use the 1.0 mm reference gap as described by the manufacturer, allowing for the required static position or dynamic travel.

05 REFERENCE

Bently Nevada 3300 XL NSv Datasheet 147385 Rev. R, applicable specification, ordering and dimensional sections.

AMIKON PRODUCT SUPPORT

+86-18020776786 INFO@AMIKON.CN **AMIKONG.COM**