3300 XL NSV

Product Data Sheet

330904-00-18-10-02-CN

Armored proximity sensing probe

CASE THREAD	CASE LENGTH	TOTAL PROBE LENGTH	CABLE EXECUTION
M8 x 1	**180 mm**	**1.0 m**	**Stainless steel armor**

Bently Nevada 330904-00-18-10-02-CN is a 3300 NSv proximity probe with a M8 x 1 standard-mount case. It measures non-contact shaft vibration and position through a matched 3300 XL NSv extension cable and Proximitor sensor. The NSv design supports restricted counterbore and side-view clearances.

01 TECHNICAL DATA

Case thread	M8 x 1
Unthreaded length	0 mm
Overall case length	180 mm
Total probe length	1.0 m
Lead construction	Stainless steel armor
Connector selection	02: miniature coaxial ClickLoc, standard cable
Connector protector	Not fitted
Agency approval selection	CN: China-specific approval option
Cable impedance	75 ohm
Cable insulation	FEP

Bently Nevada 147385 Rev. R; approval guide 108M1756 Rev. AV.

02 ADDITIONAL PRODUCT DATA

Probe tip material	Polyphenylene sulfide (PPS)
Probe case material	AISI 304 stainless steel
Probe DC resistance	4.2 +/- 0.5 ohm
Matched-chain linear range	1.5 mm; approximately 0.25 to 1.75 mm
Nominal matched-chain scale	7.87 V/mm (200 mV/mil)

03 PRODUCT FUNCTION

This execution has a 180 mm overall case, zero unthreaded length and a 1.0 m armored standard FEP-insulated lead. Connector option 02 supplies a miniature coaxial ClickLoc connection without a fitted protector. The assembly uses a PPS sensing tip and an AISI 304 stainless steel case. The CN suffix retains the China-specific approval selection documented in guide 108M1756; applicable markings and certificate scope remain tied to the supplied probe.

04 SYSTEM COMPATIBILITY

Pair the 1.0 m probe lead with a 4 m extension for a 5 m chain or a 6 m extension for a 7 m chain. Use the matching NSv Proximitor calibration. The standard 7.87 V/mm scale and 1.5 mm linear range apply to the complete matched chain under the published AISI 4140 target conditions.

05 REFERENCE

Bently Nevada 147385 Rev. R; approval guide 108M1756 Rev. AV.

AMIKON PRODUCT SUPPORT

+86-18020776786 INFO@AMIKON.CN **AMIKONG.COM**