

20 Years Automation Experience



Amikon: Your Trusted Automation Solution Expert

amikon

www.amikong.com

SPECIALIZING IN:

- **Control Systems (DCS, PLC, CNC)**
- **Panel Controllers**
- **HMI and Display Panels**
- **Drives**
- **Encoders and Resolvers**
- **Power Supplies**

Amikon Limited is a global automation parts reseller focused on hard-to-find and obsolete industrial automation products. Today we already have 20 years experience in automation area. In past time we insist to offer best service to worldwide client, In future we will also offer good quality and satisfied service again.

TK3 Proximity System Test Kit

Datasheet

Bently Nevada Machinery Condition Monitoring

178087 Rev. F



Description

The TK-3 Proximity System Test Kit simulates shaft vibration and position for calibrating Bently Nevada monitors. It verifies the operating condition of the monitor readouts as well as the condition of the proximity transducer system. A properly calibrated system ensures that the transducer inputs and the resulting monitor readings are accurate.

The TK-3 uses a removable spindle micrometer assembly to check the transducer system and position monitor calibration. This assembly features a universal probe mount that will accommodate probe diameters from 5 mm to 19 mm (0.197 in to 0.75 in). The mount holds the probe while the user moves the target toward or away from the probe tip in calibrated increments and records the output from the Proximity Sensor using a voltmeter. The spindle micrometer assembly also features a convenient magnetic base for ease of use in the field.

Vibration monitors are calibrated using the motor-driven wobble plate. A swing-arm assembly located over the wobble plate holds the proximity probe in place. This assembly uses a universal probe mount, identical to that used with the spindle micrometer assembly. By using the absolute scale factor of the proximity probe in conjunction with a multimeter, the user adjusts the probe to find a position where the desired amount of mechanical vibration (as determined by peak-to-peak DC voltage output) is present. No oscilloscope is needed.

The user can then compare a vibration monitor's reading to the known mechanical vibration signal input viewed by the proximity probe. The mechanical vibration signal from the TK-3 can range from 50 to 254 μm (2 to 10 mils) peak-to-peak.



WARNING



ROTATING MACHINERY

Risk of personal injury or equipment damage.

Keep clear of rotating components.
Avoid wearing loose clothing or objects.
Always use safety glasses and safety guards.
Check that mounting screws are secure.

Injury can result from flying debris or contact with moving parts. Keep clear of the wobble plate when operating either the TK-3e or TK-3g.

Specifications

Power Requirements

Electric	95-125 Vac, 50/60 Hz, 1A minimum 190-250 Vac, 50/60 Hz, 1A minimum
----------	---

 Power can be disconnected by disconnecting the power cable from the TK-3 unit.

Air	90 psi (6.2 bar) maximum
-----	--------------------------

Wobulator Range

Vibration Amplitude Range:	50 µm to 254 µm (2 to 10 mils) peak-to-peak.
----------------------------	--

Maximum Speed

Electric	0 to 5000 cpm ± 1000 cpm
Air	0 to 5000 cpm ± 1000 cpm
Spindle Micrometer Range	0 – 25.4 mm (0 – 1000 mils).
Target Button and Wobble Plate	AISI 4140 Alloy Steel.  Contact your nearest Sales Professional for details on special target and wobble plate materials.

Physical Size

Height	195 mm (7.68 inches)
Width	299 mm (11.8 inches)
Depth	248 mm (9.76 inches)
Weight	5.22 kg (11.5 lb)

Environmental

 Equipment is for indoor use only. Maximum altitude is 2000m.

Operational Temperature Range	0 °C to 50 °C (32 °F to 122 °F)  Temporary operation below minimum temperature is acceptable. For extended continuous use, maximum operating temperature is 40°C.
Storage Temperature Range	-18 °C to 65 °C (0 °F to 150 °F)
Humidity	95% Non-Condensing Humidity
Exposure	Designed to meet IP54 for dust and water exposure (closed)

Compliance and Certifications

FCC

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

- This device may not cause harmful interference.
- This device must accept any interference received, including interference that may cause undesired operation.

EMC

EN 61000-6-2

EN 61000-6-4

EMC Directive 2014/30/EU

RoHS

RoHS Directive 2011/65/EU

LVD

EN 61010-1

LV Directive 2014/35/EU

Ordering Information



For the detailed listing of country and product specific approvals, refer to the *Approvals Quick Reference Guide* (108M1756) available from Bently.com.

Electric Driven TK-3e

177313-AA-BB-CC

A: Scale Units

01	English
02	Metric

B: Power Cord Type

01	American
02	European
03	Brazilian

C: Agency Approvals

00	None
----	------

Air Driven TK-3g

177314-AA-BB

A: Scale Units

01	English
02	Metric

B: Agency Approvals

00	None
----	------

Accessories

168836	MDS 100 – Data Acquisition CBT (Computer Based Training) Module
--------	---

Copyright 2022 Baker Hughes Company. All rights reserved.



Bently Nevada, Proximitor and Orbit Logo are registered trademarks of Bently Nevada, a Baker Hughes business, in the United States and other countries. The Baker Hughes logo is a trademark of Baker Hughes Company. All other product and company names are trademarks of their respective holders. Use of the trademarks does not imply any affiliation with or endorsement by the respective holders.

Baker Hughes provides this information on an “as is” basis for general information purposes. Baker Hughes does not make any representation as to the accuracy or completeness of the information and makes no warranties of any kind, specific, implied or oral, to the fullest extent permissible by law, including those of merchantability and fitness for a particular purpose or use. Baker Hughes hereby disclaims any and all liability for any direct, indirect, consequential or special damages, claims for lost profits, or third party claims arising from the use of the information, whether a claim is asserted in contract, tort, or otherwise. Baker Hughes reserves the right to make changes in specifications and features shown herein, or discontinue the product described at any time without notice or obligation. Contact your Baker Hughes representative for the most current information.

The information contained in this document is the property of Baker Hughes and its affiliates; and is subject to change without prior notice. It is being supplied as a service to our customers and may not be altered or its content repackaged without the express written consent of Baker Hughes. This product or associated products may be covered by one or more patents. See [Bently.com/legal](https://www.bently.com/legal).

1631 Bently Parkway South, Minden, Nevada USA 89423
Phone: 1.775.782.3611 (US) or [Bently.com/support](https://www.bently.com/support)
[Bently.com](https://www.bently.com)

Amikon: Your Strategic Partner for Industrial Spares and Solutions

Where do the parts come from?

We utilize a global network of suppliers and sources to procure parts for you, and we perform extensive research to ensure that we're protecting you and your interests at every turn.

Facing unexpected downtime?

Count on amikon to get you back on track.

Benefit from swift dispatch, dependable lead times, and personalised service from your dedicated account manager.

At Amikon we specialise in the procurement of essential and hard-to-find automation components required to keep the manufacturing world turning.

www.amikong.com

Email: info@amikon.cn | WhatsApp: +86 18020776786

amikon