

CompactLogix™ 5370 L3 Programmable Automation Controllers



1769-L30ER, -L30ERM, -L30ER-NSE, -L33ER, -L33ERM, L36ERM, -L37ERM, -L38ERM

Features and Benefits

The CompactLogix 5370 L3 controllers deliver scalable, affordable control ideal for applications from small stand-alone equipment to high performance indexing tables, process skids, case packers and erectors, and packaging.

Machine builders and end users can take advantage of the cost-saving features of these controllers:

- Support for Integrated Motion on EtherNet/IP
- Support for Device Level Ring (DLR) network topologies
- Built-in energy storage eliminates the need for lithium batteries
- Support reuse of existing 1769 I/O
- Removable 1GB secure digital (SD) card improves data integrity
- Flexible memory options up to 3MB
- Added features for hazardous environments (NSE version)
- Support for Kinematics eliminates the need for additional robot controllers and software
- Open socket capability allows support for Modbus TCP as well as devices such as printers, barcode readers and servers

Reduce cost and time to market with CompactLogix 5370 L3 Programmable Automation Controllers.



Expanding on the scalability of the Logix family of controllers, the CompactLogix 5370 L3 programmable automation controllers (PAC) are designed to meet the growing need for a higher performance controller in a compact and affordable package.

As part of the Integrated Architecture system, the CompactLogix 5370 L3 controllers use the same programming software, network protocol, and information capabilities as all Logix controllers, providing a common development environment for all control disciplines.

Integrated Motion on EtherNet/IP

The CompactLogix 5370 L3 controller provides a strong motion solution for customers looking for performance and cost competitiveness.

- Supports up to 16 axes of integrated motion
- Together with the Kinetix 350, offers cost-effective, scalable motion solution

Network Capabilities

With dual Ethernet ports and an integrated Ethernet switch, these controllers now support Device Level Ring (DLR) network topologies, simplifying integration of components in your control system and reducing system cost:

- Provides resiliency from loss of one network connection
- Allows replacement of devices one at a time without stopping production
- Reduces the number of Ethernet switches in the control system

Features for Hazardous Environments

The No Stored Energy (NSE) version of the CompactLogix 5370 L3 offers additional features for hazardous environments found in industries such as mining and oil and gas.

- Allows safe transport of controller in and out of mining areas
- Powered down controller has less than 200uJ of residual energy stored in each component
- No consequences of arc or spark to cause an explosion in gaseous environment



CompactLogix 5370 L3 Controller Product Specifications

	1769-L30ER	1769-L30ERM	1769-L30ER-NSE	1769-L33ER	1769-L33ERM	1769-L36ERM	1769-L37ERM	1769-L38ERM
User Memory	1 MB	1 MB	1 MB	2 MB	2 MB	3 MB	4 MB	5 MB
Controller Tasks	32	32	32	32	32	32	32	32
Programs per Task	100	100	100	100	100	100	100	100
Integrated Motion	--	4 axis CIP motion position loop axis	--	--	8 axis CIP motion position loop axis	16 axis CIP motion position loop axis		
Package Size	55mm wide x 118mm high x 105mm deep							
Certifications	cULH (Class I Division 2), KCC / UL (UL 508), ULH (Class I & II, Division 2 and Class III, Divisions 1 & 2) / ATEX, CE, C-Tick, GOST-R and Marine							
Local Expansion Modules	8	8	8	16	16	30	30	30
Local Expansion I/O Points (Max)	256	256	256	512	512	960	960	960
Communication Module Additions	DeviceNet with 1769-SDN or 3rd party							
Flash Memory Card	Industrially rated and certified Secure Digital (SD) memory card (1 and 2 GB options); all controllers shipped with 1 GB card							
Servo Drives (Position Loop CIP)	--	4	--	--	8	16	16	16
Ethernet I/O IP Nodes	16	16	16	32	32	48	48	48
Virtual Axes	100	100	100	100	100	100	100	100
Feedback only, Torque, Velocity, Vhz (max CIP Motion Drives)	--	16	--	--	32	48	48	48
Axes/ms	--	2	--	--	2	2	2	2
Kinematics Support	--	yes	--	--	yes	yes	yes	yes
Software / Firmware	RSLogix 5000 V20 and RSLinx Classic V2.59 Firmware v20.1x or later						RSLogix 5000 V31 and RSLinx Classic V4.0 Firmware v31.x or later	
Conformally Coated Product Available	1769-L30ERK	1769-L30ERMK	no	1769-L33ERK	1769-L33ERMK	no	1769-L37ERMK	1769-L38ERMK

Connect with us.    

rockwellautomation.com — expanding human possibility™

AMERICAS: Rockwell Automation, 1201 South Second Street, Milwaukee, WI 53204-2496 USA, Tel: (1) 414.382.2000, Fax: (1) 414.382.4444
 EUROPE/MIDDLE EAST/AFRICA: Rockwell Automation NV, Pegasus Park, De Kleetlaan 12a, 1831 Diegem, Belgium, Tel: (32) 2 663 0600, Fax: (32) 2 663 0640
 ASIA PACIFIC: Rockwell Automation, Level 14, Core F, Cyberport 3, 100 Cyberport Road, Hong Kong, Tel: (852) 2887 4788, Fax: (852) 2508 1846

CompactLogix, Integrated Architecture, Kinetix, RSLogix, Integrated Motion on EtherNet/IP are trademarks of Rockwell Automation, inc.

Publication 1769-PP010C-EN-E - November 2019 | Supersedes Publication 1769-PP010B-EN-E - January 2013

Copyright © 2019 Rockwell Automation, Inc. All Rights Reserved. Printed in USA.