

Ordering Information



For the detailed listing of country and product-specific approvals, refer to the [Approvals Quick Reference Guide \(108M1756\)](#).

For additional technical documentation, please log in to bntechsupport.com and access the Bently Nevada Media Library.

Seismic Transmitter

177230-AA-BB-CC

A: Measurement Range

| | |
|-----------|------------------------------|
| 00 | 0 – 12.7 mm/s (0 – 0.5 in/s) |
| 01 | 0 – 25.4 mm/s (0 – 1.0 in/s) |
| 02 | 0 – 50.8 mm/s (0 – 2.0 in/s) |

B: Frequency

| | |
|-----------|--|
| 01 | 10 Hz to 1 kHz (600 to 60 kcps) RMS (Root Mean Square) |
| 02 | 3 Hz to 1 kHz (180 to 60 kcps) peak |

C: Approvals

| | |
|-----------|---|
| 05 | Multiple Approvals (CSA/NRTL/C, ATEX/IECEX) |
|-----------|---|



Only standard or common AA-BB-CC configurations are available.

Interconnect Cable without Armor

16925-AA

A: Length in feet

Order in increments of 1 foot (0.3 m)

Minimum length: 3 feet (0.91 m)
 Maximum length: 99 feet (30.2 m)
 Example: **25** = 25 feet

These standard lengths are available. You can order custom lengths at additional cost.

| Feet | Meters (approx.) |
|-----------|------------------|
| 10 | 3.1 |
| 12 | 3.6 |
| 15 | 4.5 |
| 17 | 5.0 |
| 20 | 6.0 |
| 25 | 7.6 |
| 30 | 9.0 |
| 99 | 30.0 |

Interconnect Cable with Armor

16710-AA

A: Length in feet

Order in increments of 1 foot (0.3 m)

Minimum length: 3 feet (0.91 m)
 Maximum length: 99 feet (30.2m)
 Example: **25** = 25 feet

These standard lengths are available. You can order custom lengths at additional cost.

| Feet | Meters (approx.) |
|-----------|------------------|
| 08 | 2.4 |
| 10 | 3.1 |
| 12 | 3.6 |
| 15 | 4.5 |
| 17 | 5.0 |
| 20 | 6.0 |
| 30 | 9.0 |
| 99 | 30.0 |