

### Remote I/O Units



A Remote I/O Unit connects VersaMax I/O modules to a host PLC or computer via a variety of networks, which makes it easy to include VersaMax I/O in Genius, PROFIBUS-DP, DeviceNet, or Ethernet installations. Together, the Remote I/O Unit and its modules form an I/O station capable of providing up to 256 points of I/O.

	<b>IC200GBI001</b>	<b>IC200PBI001</b>
	<b>Genius Network Interface Unit</b>	<b>Remote I/O PROFIBUS-DP Network Interface Unit (Slave)</b>
<b>Product Name</b>		
<b>Lifecycle Status</b>	Active	Active
<b>Protocol Supported</b>	Genius	PROFIBUS DP
<b>Distance</b>	1372 to 2286 meters - 38.4 Kbaud supports a maximum of 16 devices. 1067 to 1372 meters 76.8 Kbaud supports a maximum of 32 devices. 609 to 1067 meters - 153.6 Kbaud extended supports a maximum of 32 devices. Less than 609 meters 153.6 Kbaud standard or 153.6 Kbaud extended supports a maximum of 32 devices.	9.6Kbits - 1,200 meters 19.2Kbits - 1,200 meters 93.75Kbits - 1,200 meters 187.5Kbits - 600 meters 500Kbits - 400 meters 1.5Mbits - 200 meters 3Mbits; 6Mbits; 12Mbits - 100 meters
<b>I/O Discrete Points</b>	1024 Inputs and 1024 Outputs	375 bytes maximum. Up to 244 bytes of inputs or 244 bytes of outputs
<b>I/O Analog Words</b>	64 Analog In and 64 Analog Out	375 bytes maximum. Up to 244 bytes of inputs or 244 bytes of outputs
<b>I/O Data</b>	128 bytes in and 128 out per bus scan	375 bytes maximum. Up to 244 bytes of inputs or 244 bytes of outputs.
<b>I/O Data Update Rate</b>	N/A	N/A
<b>Network Topology</b>	Bus	Linear bus, terminated at both ends. Stubs are possible.
<b>Transmission Media</b>	Shielded, twisted pair, fiber optic (external option)	Shielded, twisted pair cable
<b>Connector</b>	Removable Connector	9-pin D-sub connector
<b>User Diagnostic Data</b>	Yes	2 bytes of status/control, 5 bytes of standard PROFIBUS diagnostics
<b>Number of Modules</b>	8 per NIU/station	8 per NIU/station
<b>Redundancy</b>	Full media and hardware redundancy supported	N/A
<b>5V Backplane Current Consumption (mA)</b>	250	250
<b>3.3V Backplane Current Consumption (mA)</b>	10	10
<b>Dimensions (W x H x D)</b>	133.4 mm (5.25 in) x 85.9 mm (3.38 in) not including the height of power supply	133.4 mm (5.25 in) x 85.9 mm (3.38 in) not including the height of power supply