

Ordering Information



For the detailed listing of country and product specific approvals, refer to the *Approvals Quick Reference Guide* (108M1756) available from Bently.com.

330525-AA

A: Agency Approval Option

0 0	None Required
0 1	CSA/NRTL/C
0 2	SIRA/CENELEC

106765-AA Interconnect Cable

A: Length (in meters)

Minimum length	1 meter (3.3 feet)
Maximum length	25 meters (82 feet)

Order in increments of 3 meters.

Terminal Housing

Terminal Housing for terminating Velomitor XA Sensor cable to bulk cable listed above. The Terminal Housing provides local connection of the Velomitor XA Sensor signal wires to the monitor field wiring. Each Terminal Housing can accommodate up to 2 Velomitor XA Sensor Cables.

106769-AA

A: Conduit Fitting Option

0 0	No fittings supplied
0 1	One ¼ NPT fitting
0 2	Two ¼ NPT fittings

Accessories

100076	330500/330525 Velomitor Sensor and Velomitor XA Sensor User Guide
02173007	Bulk cable; two-conductor twisted, shielded. 22 AWG cable without connectors or terminal lugs. Specify length in feet.
103537-01	Terminal Mounting Block. Provides simple field wiring connection and can be mounted inside any standard Proximitor Sensor housing. One terminal mounting block is needed for each Velomitor XA Sensor connection.
03839144	Splash-resistant boot cover for interconnect cable assembly. The boot is made from fluorosilicone elastomer. Boot color is blue.
03839142	Bottom clamp used to secure the boot to the Velomitor XA Sensor case.
03839143	Top clamp used to secure the boot to the interconnect cable assembly.