

Ordering Information



For the detailed listing of country and product-specific approvals, refer to the [Approvals Quick Reference Guide \(108M1756\)](#).

For additional technical documentation, please log in to bntechsupport.com and access the Bently Nevada Media Library.

330400 Accelerometer

330425 Accelerometer

Part Number-AA-BB

A: Mounting Thread Option

0 1 ¼-28 UNF integral stud

0 2 M8 X 1 integral stud

B: Agency Approval Option

0 0 None

0 5 Multiple approvals (CSA, ATEX, IECEx,)

Interconnect Cables

Part Number-AA

| A: | Cable Length Option in feet |
|----|--|
| | For the cables listed below, order in increments of 1.0 ft (305 mm). |

Examples:

1 5 = 15 ft (4.57 m)

2 0 = 20 ft (6.10 m)

The following are standard lengths

| Feet | Metres (approx.) |
|------|------------------|
| 6 | 1.8 |
| 8 | 2.4 |
| 10 | 3.0 |
| 12 | 3.6 |
| 15 | 4.5 |
| 17 | 5.0 |
| 20 | 6.0 |
| 25 | 7.6 |
| 50 | 15.2 |
| 99 | 30.0 |



Non-standard/custom lengths can also be ordered at additional cost.

Cable Part Numbers

| | |
|--------|--|
| 130539 | 3-conductor shielded 18 AWG (1.0 mm ²) cable with 3-socket plug and fluorosilicone elastomer boot at one end, terminal lugs at the other end. Minimum length of 2.0 ft (0.6 m), maximum length of 99 ft (30 m). A manual is available to assist with installation of this cable (part number 133080-01). |
| 16925 | 3-conductor shielded 22 AWG (0.5 mm ²) cable with 3-socket plug at one end, terminal lugs at the other end. Minimum length of 2.0 ft (0.6 m), maximum length of 99 ft (30 m). |