

Remote I/O

Remote I/O IS1+ HART analogue universal module

for Zone 2 Ex i

9468/33-08-10 Art. No. 210660



- Eight channels can be used individually as inputs or outputs
- Intrinsically safe Ex ia IIC inputs/outputs with line fault monitoring
- Module in Zone 2, Cl. I, II, Div. 2 can be hot swapped

MY R. STAHL 9468B



The 9468/33 series HART Analog Universal Module for Zone 2, Cl. I, II, Div. 2 has eight channels that can be used individually for Ex i operating two-/three-conductor HART transmitters, four-conductor transmitters or control valves/positioners with 0/4 to 20 mA signals. HART communication is bidirectional. All inputs/outputs are short-circuit proof, galvanically separated from the system and individually monitored to check for line faults.

Technical Data

Explosion Protection

Application range (zones)	2
Application range (Zone) note	A suitable enclosure in accordance with the area of application must be used. Refer to the operating instructions.
Ex interface zone	0, 1, 2, 20, 21, 22
IECEX gas certificate	IECEX DEK 12.0054X
IECEX gas explosion protection	Ex ec ia [ia Ga] IIC T4 Gc
IECEX dust certificate	IECEX DEK 12.0054X
IECEX dust explosion protection	[Ex ia Da] IIIC
ATEX gas certificate	DEKRA 12 ATEX0173 X
ATEX gas explosion protection	Ex II 3 (1) G Ex ec ia [ia Ga] IIC T4 Gc
ATEX dust certificate	DEKRA 12 ATEX0173 X
ATEX dust explosion protection	Ex II (1) D [Ex ia Da] IIIC
FMus certificate	FM17US0332X
cFM certificate	FM16CA0134X
Marking cFMus	NI, Class I, Div. 2, Groups A,B,C,D; Class I, Zone 2, AEx/Ex nA ia [ia] IIC AIS Class I,II,III, Div. 1, Groups A,B,C,D,E,F,G; T4 at Ta = 75°C See Doc. 9468 6 031 002 1
Certificates	ATEX (DEK), Brazil (ULB), Canada (FM), China (NEPSI), IECEX (DEK), India (PESO), Korea (KTL), USA (FM)
Ship approval	ABS, BVIS, EU RO MR (DNV), KR, LR
Declaration of conformity	ATEX (EUK), China (CCC)
Installation	Zone 2, Cl. I, Div. 2 and in the safe area
Further information	see operating instructions and certificate

Safety Data

Max. voltage U_o/V_{oc}	24.4 V
---------------------------	--------

Remote I/O

Remote I/O IS1+ HART analogue universal module

for Zone 2 Ex i

9468/33-08-10 Art. No. 210660



Safety Data

Max. current I_o (2-conductor)	80 mA																											
Max. power P_o (2-conductor)	488 mW																											
Max. current I_o (3-wire)	81.8 mA																											
Max. power P_o (3-wire)	499 mW																											
Internal capacitance	Negligible																											
Internal inductance	Negligible																											
Max. connectable inductance L_o /capacitance C_o																												
2-conductor input/output																												
IIC	L_o [mH]	3.8	2	1	0.5	0.2																						
	C_o [nF]	53	59	71	88	119																						
IIB	L_o [mH]	23	10	2	1	0.5	0.2	0.1	0.05																			
	C_o [nF]	370	430	430	470	550	700	860	890																			
3-conductor input																												
IIC	L_o [mH]	3.6	2	1	0.5	0.2																						
	C_o [nF]	53	58	70	87	119																						
IIB	L_o [mH]	21	10	2	1	0.5	0.2	0.1	0.05																			
	C_o [nF]	380	420	420	470	550	700	860	890																			
Limiting values																												
4-conductor transmitters	<p>U_o, I_o, P_o, C_i und L_i are negligible. Maximum connectable safety characteristic values during operation with active 4-conductor transmitters:</p> <table border="1"> <thead> <tr> <th>Max. input voltage U_i [V]</th> <th>Max. input current I_i [mA]</th> <th>Max. ambient temperature T_{amb} [°C]</th> </tr> </thead> <tbody> <tr> <td>28</td> <td>150</td> <td>55</td> </tr> <tr> <td>28</td> <td>140</td> <td>60</td> </tr> <tr> <td>28</td> <td>130</td> <td>65</td> </tr> <tr> <td>28</td> <td>115</td> <td>70</td> </tr> <tr> <td>28</td> <td>105</td> <td>75</td> </tr> </tbody> </table>										Max. input voltage U_i [V]	Max. input current I_i [mA]	Max. ambient temperature T_{amb} [°C]	28	150	55	28	140	60	28	130	65	28	115	70	28	105	75
Max. input voltage U_i [V]	Max. input current I_i [mA]	Max. ambient temperature T_{amb} [°C]																										
28	150	55																										
28	140	60																										
28	130	65																										
28	115	70																										
28	105	75																										

Electrical Data

Number of channels	8 Ex i inputs/outputs
Channels	each with adjustable parameters as input or output (3-wire, 4-wire transmitters, or active mA-sources occupy 2 channels)
Nominal signal	4 to 20 mA 0 to 20 mA
Min. signal	0 mA
Supply voltage	16 V, at 20 mA for 2-conductor transmitters
Communication signal	HART protocol
Connection Ex i field signals	Pluggable, blue terminals, 16-pole, 2.5 mm ² , screw- or spring-type versions with lock

Remote I/O

Remote I/O IS1+ HART analogue universal module

for Zone 2 Ex i

9468/33-08-10 Art. No. 210660



Electrical Data

Notes	In order to operate an active 4-wire HART transmitter, a 9164 must be connected between each channel. 9164 is not required when operating 4-wire transmitter without HART communication.
-------	--

Signal transmission		Filter time constant (adjustable parameters)		
		Small	Medium	50 Hz, 60 Hz
	Measurement discrimination in the range 4 to 20 mA	14.75 bit (with HART: 12.75 bit)	14.75 bit	14.75 bit
	Maximum delay from signal/internal bus	32 ms	120 ms	500 ms

Auxiliary Power

Power supply connection	BusRail types 9494
Auxiliary power version	Intrinsically safe Ex ia via BusRail
Current consumption	220 mA (at 20 mA per channel)
Max. power consumption	5.3 W (at 20 mA/channel)
Max. power dissipation outputs	3.7 W (at 20 mA, 500 Ω/channel)
Max. power dissipation inputs	2.7 W (at 20 mA/channel)

Galvanic Isolation

Test voltage for galvanic separation	Acc. to standard EN 60079-11
Auxiliary power/system components	≥ 1500 V AC
I/O module / I/O module	≥ 500 V AC
I/O channels/system components	≥ 500 V AC
I/O channels / ground (PA)	≥ 500 V AC

Input

Max. signal for input	23.5 mA
Max. input short-circuit current	24 mA
Max. input resistance	14.1 Ω per channel

Output

Output step response (10 to 90%)	40 ms
Max. output short-circuit current	22,8 mA (4 ... 20 mA) 23,5 mA (0 ... 20 mA)
Max. signal for output	22.8 mA (4 to 20 mA) 23.5 mA (0 to 20 mA)
Output max. load resistance	750 ohm at 20 mA 700 Ω at 21.8 mA
Open-circuit voltage U_a	22.5 V

Device Specific Data

Signal type	Output Input
Diagnostics message module	ON OFF
Signal filter module	50 Hz large 60 Hz large medium small

Remote I/O

Remote I/O IS1+ HART analogue universal module

for Zone 2 Ex i

9468/33-08-10 Art. No. 210660



Device Specific Data

Scan HART live list module	ON OFF
Signal range	0 ... 20 mA 4 ... 20 mA
Input measuring range	3.6 to 21 mA (acc. to NAMUR) 2.4 to 22.8 or 23.5 mA
Line fault monitoring	OFF ON
Input behaviour in case of error	110% 100% 0% -10% Alarm code, keep last value
Output behaviour in case of error	-10% 0% 100% 110% Keep last value
Cyclical data transmission of HART variants	No 8HV 4HV
Retrievable parameters	Type Software revision Serial number Manufacturer Hardware revision
LED module requires maintenance	"M/S" LED, blue
LED operating conditions	"RUN" LED, green
LED channel error	without
Module status and alarms	Internal bus error primer / redundant No response from IOM Configuration does not correspond to the module Hardware error Excess temperature Slot error Module requires maintenance
Signal status bit	1 = Signal valid 0 = Signal interrupted
Wire breakage input	< 2,4 mA / 3,6 mA (adjustable parameters, at 4 to 20 mA)
Short circuit input	> 23.5 mA > 22.8 mA / > 21 mA (adjustable parameters)
Wire breakage output	Terminal voltage > 16 V (response range 16 ... 16.5 V) or output current can not longer be set
Short circuit output	Output load < 60 Ω (response range 40 ... 60 Ω)
Influence of ambient temperature	< 0,03 % / 10 K
Accuracy of measurement	
Error of measurement with filter time constant	Small Medium 50 Hz, 60 Hz

Remote I/O

Remote I/O IS1+ HART analogue universal module

for Zone 2 Ex i

9468/33-08-10 Art. No. 210660



Maximum error of measurement	0.075% (12 µA at 4 to 20 mA)	0.05% (8 µA at 4 to 20 mA)	0.05% (8 µA at 4 to 20 mA)
------------------------------	---------------------------------	-------------------------------	-------------------------------

Note: All information in % of the signal span at 23 °C

Diagnosics

LED group error	"ERR" LED, red
-----------------	----------------

Ambient Conditions

Ambient temperature °C	-40 °C ... +75 °C Observe operating instructions
Ambient temperature °F	-40°F ... +167°F Observe operating instructions
Storage temperature °C	-40 °C ... +80 °C
Storage temperature °F	-40°F ... +176°F
Max. operating altitude	< 2000 m
Max. operating altitude	2000 m
Max. relative humidity	95% (without condensation)
Max. relative humidity	95 %
Max. relative humidity note	without condensation
Shock (semi-sinusoidal)	(IEC EN 60068-2-27) 15 g (3 shocks per axis and direction)
Vibration (sinusoidal)	(IEC EN 60068-2-6) Frequency range 2 ... 13.2 Hz Amplitude 1 mm (peak value) Frequency range 13.2 ... 100 Hz Acceleration amplitude 0.7 g
Electromagnetic compatibility	Tested to the following standards and regulations: EN 61326-1 (2006) IEC 61000-4-1 to 61000-4-6, NAMUR NE 21

Mechanical Data

Degree of protection (IP) (IEC 60529)	IP20
Module enclosure	Polyamide 6GF
Fire resistance (UL 94)	V2
Pollutant class	Corresponds to G3
Width	96.5 mm
Width, inches	3.8 in
Depth	68 mm
Length	128 mm
Length in inches	5.04 in
Mounting depth in inches	2.64 in
Weight	275 g
Weight	0.61 lb

Mounting / Installation

Mounting orientation	Horizontal Vertical
----------------------	------------------------