

Cable Part Numbers

Part number	Description
† NOTE: Use 'AA' in the part numbers below to specify the length (in feet) of the cable you want to order.	
02173034	<p>Splash-Proof Interconnect Cable</p> <p>Recommended for high electromagnetic noise environment and European Conformance (CE).</p> <p>Shielded 0.382 mm² (22 AWG) cable with a splash proof boot over a female connector at the transducer end and flush cut at the monitor end. Temperature range -55 to 125°C (-67 to 257°F). See Graphs and Figures.</p>
CB2W100-AAA†	<p>Splash-Proof Interconnect Cable</p> <p>Shielded 0.382 mm² (22 AWG) cable with splash proof over molded boot, blunt cut at the monitor end. Temperature range -50 to 200°C (-58 to 392°F). See Graphs and Figures.</p> <p>Standard lengths:</p> <ul style="list-style-type: none"> 01515 ft (4.5 m) 03232 ft (9.8 m) 06464 ft (19.5 m) 112112 ft (34.1 m) 125125 ft (38.1 m) 150150 ft (45.7 m) 200200 ft (61.09 m)

Part number	Description
9571-AA†	<p>Standard Interconnect Cable</p> <p>Shielded 0.382 mm² (22 AWG) cable with a moisture resistant female connector at the transducer end and ring lugs at the monitor end. Temperature range -29 to 121°C (-20 to 250°F). See Graphs and Figures.</p> <p>Minimum length 2 ft (0.60 m); maximum length 99 ft (30 m).</p>
84661-AA†	<p>Standard Armored Interconnect Cable</p> <p>Stainless steel armor over shielded 0.382 mm² (22 AWG) cable with a moisture resistant female connector at the transducer end and ring lugs at the monitor end. Temperature range -29 to 121°C (-20 to 250°F). See Graphs and Figures.</p> <p>Minimum length 3 ft (0.91 m); maximum length 96 ft (29 m).</p>
89477-AA†	<p>Right Angle Interconnect Cable</p> <p>Shielded 0.963 mm² (18 AWG) cable with a moisture resistant right angle female connector at the transducer end and ring lugs at the monitor end. Temperature range -29 to 121°C (-20 to 250°F). See Graphs and Figures.</p>