



SIMATIC S7-300, CP 341 Communications processor with RS422/485 interface
incl. configuration package on CD

General information	
Product type designation	CP 341
Supply voltage	
Rated value (DC)	
• 24 V DC	Yes
Input current	
from supply voltage L+, max.	100 mA
from backplane bus 5 V DC, max.	70 mA
Power loss	
Power loss, typ.	1.6 W
Power loss, max.	2.4 W
Interfaces	
Interfaces/bus type	RS 422 / 485 (X.27)
Number of interfaces	1; Isolated
Transmission rate, min.	0.3 kbit/s
Transmission rate, max.	115.2 kbit/s
Point-to-point connection	
• Cable length, max.	1 200 m
• supported printers	Serial printers
• Connector type	15-pin sub D socket
Integrated protocol driver	
— 3964 (R)	Yes; not with RS 485
— ASCII	Yes
— RK 512	Yes; not with RS 485
Telegram length, max.	
— 3964 (R)	4 096 byte
— ASCII	4 096 byte
— RK 512	4 096 byte
Transmission rate, RS 422/485	
— with 3964 (R) protocol, max.	115.2 kbit/s
— with ASCII protocol, max.	115.2 kbit/s
— with printer driver, max.	115.2 kbit/s
— with RK 512 protocol, max.	115.2 kbit/s
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	60 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C

Software	
Block	
• FB length in RAM, max.	6 100 byte; Data communication, sending and receiving
connection method	
Design of electrical connection for supply voltage	3 screw-type terminals: L+, M, GND
Dimensions	
Width	40 mm
Height	125 mm
Depth	120 mm
Weights	
Weight, approx.	300 g
last modified: 3/12/2024 	