

## Ordering Information



For the detailed listing of country and product-specific approvals, refer to the [Approvals Quick Reference Guide \(108M1756\)](#).

For additional technical documentation, please log in to [bntechsupport.com](http://bntechsupport.com) and access the Bently Nevada Media Library.

## 3300 NSv Proximity Probes

**330901** 3300 NSv Probe, 1/4-28 UNF thread, without armor

**330902** 3300 NSv Probe, 1/4-28 UNF thread, with armor

**330908** 3300 NSv Probe, 3/8-24 UNF thread, without armor

**330909** 3300 NSv Probe, 3/8-24 UNF thread, with armor

**Part Number-AA-BB-CC-DD-EE**

### A: Unthreaded Length Option



Unthreaded length must be at least 0.7 inch less than the case length.

Order in increments of 0.1 in

Length configurations:

Maximum unthreaded length: 9.2 in

Minimum unthreaded length: 0.0 in

Example: **04** = 0.4 in

### B: Overall Case Length Option

Order in increments of 0.1 in

Threaded length configurations:

Maximum case length: 9.9 in

Minimum case length: 0.8 in

Example: **2 4** = 2.4 in

### C: Total Length Option

**05** 0.5 meter (20 in)

**10** 1.0 meter (39 in)

**50** 5.0 meters (16.4 feet)

**70** 7.0 meters (23.0 feet)

### D: Connector and Cable-Type Option

**01** Miniature coaxial ClickLoc connector with connector protector, standard cable

**02** Miniature coaxial ClickLoc connector, standard cable

**11** Miniature coaxial ClickLoc connector with connector protector, FluidLoc cable

**12** Miniature coaxial ClickLoc connector, FluidLoc cable

### E: Agency Approval Option

**00** Not required

**05** Multiple Approvals

## 3300 NSv Proximity Probes, Metric

**330903** 3300 NSv Probe, M8X1 thread, without armor

**330904** 3300 NSv Probe, M8X1 thread, with armor

**330905** 3300 NSv Probe, M10X1 thread, without armor

**330910** 3300 NSv Probe, M10X1 thread, with armor

**Part Number-AA-BB-CC-DD-EE**

**A: Unthreaded Length Option**



Unthreaded length must be at least 20 mm less than the case length.

Order in increments of 10 mm.

Length configuration:

Maximum unthreaded length:

230 mm

Minimum unthreaded length:

0 mm

Example:

**06** = 60 mm

**B: Overall Case Length Option**

Order in increments of 10 mm.

Metric thread configurations:

Maximum length: 250 mm

Minimum length: 20 mm

Example: **06** = 60 mm

**C: Total Length Option**

**05** 0.5 meter (20 in)

**10** 1.0 meter (39 in)

**50** 5.0 meters (16.4 feet)

**70** 7.0 meters (23.0 feet)

**D: Connector and Cable-Type Option**

**01** Miniature coaxial ClickLoc connector with connector protector, standard cable

**02** Miniature coaxial ClickLoc connector, standard cable

**11** Miniature coaxial ClickLoc connector with connector protector, FluidLoc cable

**12** Miniature coaxial ClickLoc connector, FluidLoc cable

**E: Agency Approval Option**

**00** Not required

**05** Multiple Approvals

**3300 NSv Reverse Mount Probe**

**330906-02-12-CC-DD-EE** 3/8-24 UNF threads

**330907-05-30- CC-DD-EE** M10X1 threads

**C: Total Length Option**

**05** 0.5 meter (20 in)

**10** 1.0 meter (39 in)

**50** 5.0 meters (16.4 feet)

**70** 7.0 meters (23.0 feet)

**D: Connector Option**

**02** Miniature coaxial ClickLoc connector, standard cable

**12** Miniature coaxial ClickLoc connector, FluidLoc cable

**E: Agency Approval Option**

**00** Not required

|    |                                                                                                                                                                                                                                                                                                                                                                                                                               |
|----|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 05 | <p>Multiple Approvals</p> <div>  <p>For a shorter delivery time, order commonly stocked probes. Currently, stocked probes consist of the following part numbers: 330901-00-24-05-02-00, 330901-00-90-05-02-00, 330902-00-50-05-02-00, 330902-00-95-05-02-00, 330903-00-02-10-02-00, 330903-00-03-10-02-00, 330906-02-12-05-02-00.</p> </div> |
|----|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## 3300 XL NSv Proximitors Sensor

### 330980-AA-BB

#### A: Total Length and Mounting Option

|    |                                                                         |
|----|-------------------------------------------------------------------------|
| 50 | 5.0 meters (16.4 feet) system length, panel mount                       |
| 51 | 5.0 meters (16.4 feet) system length, DIN mount                         |
| 52 | 5.0 meters (16.4 feet) system length, no mounting hardware <sup>1</sup> |
| 70 | 7.0 meters (23.0 feet) system length, panel mount                       |
| 71 | 7.0 meters (23.0 feet) system length, DIN mount                         |
| 72 | 7.0 meters (23.0 feet) system length, no mounting hardware <sup>1</sup> |

#### B: Agency Approval Option

|    |                    |
|----|--------------------|
| 00 | Not required       |
| 05 | Multiple approvals |

## 3300 NSv Extension Cable

### 330930-AAA-BB-CC



Make sure that the extension cable length and the probe length, when added together, equal the Proximitors Sensor total length.

#### A: Cable Length Option

|     |                        |
|-----|------------------------|
| 040 | 4.0 meters (13.1 feet) |
| 045 | 4.5 meters (14.8 feet) |
| 060 | 6.0 meters (19.7 feet) |
| 065 | 6.5 meters (21.3 feet) |

#### B: Connector and Cable Option

|    |                                                                          |
|----|--------------------------------------------------------------------------|
| 00 | Without stainless steel armor                                            |
| 01 | With stainless steel armor, with FEP jacket                              |
| 02 | With stainless steel armor, without FEP jacket                           |
| 03 | Without stainless steel armor, with connector protector                  |
| 04 | With stainless steel armor, with FEP jacket, with connector protector    |
| 05 | With stainless steel armor, without FEP jacket, with connector protector |
| 06 | FluidLoc cable without stainless steel armor                             |
| 07 | FluidLoc cable with stainless steel armor, with FEP jacket               |
| 08 | FluidLoc cable with stainless steel armor, without FEP jacket            |
| 09 | FluidLoc without stainless steel armor, with connector protector         |