

## Remote I/O

### Remote I/O IS1+ Temperature input module

for Zone 1 Ex i

9482/32-08-11 Art. No. 217643



- Eight channels for resistance temperature detectors, potentiometers, thermocouples, mV sensors and joysticks
- Ex ia intrinsically safe inputs with line fault monitoring and LED error indication
- Module in Zone 1 can be replaced without having to disconnect the power supply (i.e. hot-swapped)

MY R. STAHL 9482A



The 9482 temperature input module for Zone 1 has eight channels for Ex i operation of resistance temperature detectors with 2-, 3- or 4-conductor connection and thermocouples. Sensors that comply with DIN, IEC and GOST are supported as well as resistance transmitters up to 10 k $\Omega$  and also joysticks for rapid 4-channel operation. Earthed thermocouples can be connected. Reference junction compensation can be performed internally or externally.

## Technical Data

### Explosion Protection

|                                 |  |
|---------------------------------|--|
| Application range (zones)       | 1, 2   |
| Application range (Zone) note   | An enclosure that is suitable for the application must be used.<br>See operating instructions.   |
| Ex interface zone               | 0, 1, 2, 20, 21, 22  |
| IECEX gas certificate           | IECEX DEK 13.0046X   |
| IECEX gas explosion protection  | Ex ia [ia Ga] IIC T4 Gb  |
| IECEX dust certificate          | IECEX DEK 13.0046X   |
| IECEX dust explosion protection | [Ex ia Da] IIIC  |
| ATEX gas certificate            | DEKRA 13 ATEX 0140 X   |
| ATEX gas explosion protection   | Ex II 2 (1) G Ex ia [ia Ga] IIC T4 Gb  |
| ATEX dust certificate           | DEKRA 13 ATEX 0140 X   |
| ATEX dust explosion protection  | Ex II (1) D [Ex ia Da] IIIC  |
| FMus certificate                | FM17US0332X  |
| cFM certificate                 | FM16CA0134X  |
| Marking cFMus                   | IS, Class I, Div. 1, Groups A,B,C,D;<br>Class I, Zone 1, AEx/Ex ia [ia] IIC<br>AIS Class I,II,III, Div. 1, Groups A,B,C,D,E,F,G;<br>T4 at Ta = 75°C<br>See Doc. 9482 6 031 001 1 |
| Certificates                    | ATEX (DEK), Brazil (ULB), Canada (FM), China (NEPSI), IECEX (DEK), India (PESO), Korea (KTL), USA (FM)   |
| Ship approval                   | ABS, BVIS, EU RO MR (DNV), KR, LR  |
| Declaration of conformity       | ATEX (EUK), China (CCC)  |
| Installation                    | Zones 1, 2 and safe areas  |
| Further information             | See operating instructions and certificate   |

### Safety Data

|                      |            |
|----------------------|------------|
| Internal capacitance | Negligible |
|----------------------|------------|

#### Safety Data

|  |  |             |             |      |      |      |      |       |
|--|--|-------------|-------------|------|------|------|------|-------|
| Internal inductance                                  | Negligible   |             |             |      |      |      |      |       |
| Notes  | For proof of intrinsic safety, the safety data must be used in accordance with the combination of connections and the corresponding sensor.<br>For further information and combinations, see the operating instructions. |             |             |      |      |      |      |       |
| Combination of connections 1                         |  |             |             |      |      |      |      |       |
| Sensors  | Up to 8 resistance temperature detectors or resistance transmitters  |             |             |      |      |      |      |       |
| Note   | No thermocouple/mV sensor connected  |             |             |      |      |      |      |       |
| Installation type                                    | Insulated  |             |             |      |      |      |      |       |
| Max. output voltage $U_o$ ext                        | 6.42 V   |             |             |      |      |      |      |       |
| Max. current $I_o$                                   | 2-conductor  | 3-conductor | 4-conductor |      |      |      |      |       |
|  | 6.5 mA   | 7.8 mA      | 9.8 mA      |      |      |      |      |       |
| Max. power $P_o$                                     | 2-conductor  | 3-conductor | 4-conductor |      |      |      |      |       |
|  | 10.5 mW  | 12.5 mW     | 15.7 mW     |      |      |      |      |       |
| Max. connectable inductance $L_o$ /capacitance $C_o$ |  |             |             |      |      |      |      |       |
| IIC  | $L_o$ [mH]   | 100         | 50          | 20   | 2    | 0.2  | 0.02 | 0.002 |
|  | $C_o$ [ $\mu$ F]   | 1.1         | 1.2         | 1.4  | 2.0  | 3.2  | 7.0  | 25    |
| IIB/IIIC   | $L_o$ [mH]   | 100         | 50          | 20   | 2    | 0.2  | 0.02 | 0.002 |
|  | $C_o$ [ $\mu$ F]   | 5           | 6.3         | 7.1  | 10   | 19   | 51   | 570   |
| Combination of connections 2                         |  |             |             |      |      |      |      |       |
| Sensors  | Up to 8 thermocouples or mV sensors  |             |             |      |      |      |      |       |
| Note   | Can be connected simultaneously to resistance temperature detectors and resistance transmitters an external reference junction   |             |             |      |      |      |      |       |
| Installation type                                    | Earthed  |             |             |      |      |      |      |       |
| Reference junction                                   | Internal/external  |             |             |      |      |      |      |       |
| Thermocouple/mV sensor                               |  |             |             |      |      |      |      |       |
| Max. output voltage $U_o$ ext                        | 12.92 V  |             |             |      |      |      |      |       |
| Max. current $I_o$                                   | 25.0 mA  |             |             |      |      |      |      |       |
| Max. power $P_o$                                     | 81.0 mW  |             |             |      |      |      |      |       |
| Max. connectable inductance $L_o$ /capacitance $C_o$ |  |             |             |      |      |      |      |       |
| IIC  | $L_o$ [mH]   | 72          | 50          | 10   | 2    | 1    | 0.5  | 0.2   |
|  | $C_o$ [ $\mu$ F]   | 0.17        | 0.22        | 0.34 | 0.46 | 0.53 | 0.62 | 0.78  |
| IIB/IIIC   | $L_o$ [mH]   | 100         | 20          | 5    | 1    | 0.5  | 0.2  | 0.1   |
|  | $C_o$ [ $\mu$ F]   | 1.2         | 1.6         | 2.1  | 3.0  | 3.5  | 4.5  | 5.7   |
| Resistance sensor                                    | See values, combination of connections 3   |             |             |      |      |      |      |       |
| External reference junctions                         | See values, combination of connections 4   |             |             |      |      |      |      |       |
| Combination of connections 3                         |  |             |             |      |      |      |      |       |
| Sensors  | Up to 8 resistance temperature detectors/resistance transmitters and/or thermocouples/mV sensors   |             |             |      |      |      |      |       |
| Note   | Any combination of sensor types is possible when simultaneously connected  |             |             |      |      |      |      |       |
| Installation type                                    | Resistance temperature detector and resistance transmitter insulated/<br>thermocouple and mV sensor earthed  |             |             |      |      |      |      |       |
| Resistance sensor reference junction                 | Internal/external  |             |             |      |      |      |      |       |
| Max. output voltage $U_o$ ext                        | 12.92 V  |             |             |      |      |      |      |       |

# Remote I/O

## Remote I/O IS1+ Temperature input module for Zone 1 Ex i

9482/32-08-11 Art. No. 217643



|  |   |             |             |             |      |      |      |      |
|--|---|-------------|-------------|-------------|------|------|------|------|
| Max. current $I_o$                                   |   | 2-conductor | 3-conductor | 4-conductor |      |      |      |      |
|  |   | 13.1 mA     | 15.7 mA     | 19.6 mA     |      |      |      |      |
| Max. power $P_o$                                     |   | 2-conductor | 3-conductor | 4-conductor |      |      |      |      |
|  |   | 42.2 mW     | 50.6 mW     | 63.3 mW     |      |      |      |      |
| Max. connectable inductance $L_o$ /capacitance $C_o$ | $L_o$ [mH]  | 100         | 50          | 20          | 5    | 1    | 0.5  | 0.2  |
|  | $C_o$ [ $\mu$ F]  | 0.19        | 0.25        | 0.31        | 0.40 | 0.54 | 0.63 | 0.78 |
| IIC  | $L_o$ [mH]  | 100         | 20          | 10          | 2    | 1    | 0.5  | 0.1  |
|  | $C_o$ [ $\mu$ F]  | 1.3         | 1.7         | 1.9         | 2.5  | 3.0  | 3.5  | 5.7  |
| Thermocouple/mV sensor                               | See values, combination of connections 2  |             |             |             |      |      |      |      |
| External reference junctions                         | See values, combination of connections 4  |             |             |             |      |      |      |      |
| Combination of connections 4                         |   |             |             |             |      |      |      |      |
| Sensors  | External reference junction   |             |             |             |      |      |      |      |
| Note   | When connected to thermocouples/mV sensors, also simultaneously connectable to resistance temperature detectors/resistance transmitters |             |             |             |      |      |      |      |
| Installation type                                    | Insulated   |             |             |             |      |      |      |      |
| Reference junction                                   | External (3-conductor)  |             |             |             |      |      |      |      |
| External reference junction                          |   |             |             |             |      |      |      |      |
| Max. output voltage $U_o$ ext                        | 12.92 V   |             |             |             |      |      |      |      |
| Max. current $I_o$                                   | 17.4 mA   |             |             |             |      |      |      |      |
| Max. power $P_o$                                     | 56.2 mW   |             |             |             |      |      |      |      |
| Max. connectable inductance $L_o$ /capacitance $C_o$ | $L_o$ [mH]  | 66          | 50          | 20          | 5    | 1    | 0.5  | 0.2  |
|  | $C_o$ [ $\mu$ F]  | 0.17        | 0.21        | 0.29        | 0.39 | 0.53 | 0.62 | 0.78 |
| IIC  | $L_o$ [mH]  | 100         | 20          | 5           | 1    | 0.5  | 0.2  | 0.1  |
|  | $C_o$ [ $\mu$ F]  | 1.2         | 1.6         | 2.1         | 2.9  | 3.5  | 4.5  | 5.7  |
| IIB/IIIC   |   |             |             |             |      |      |      |      |
| Resistance sensor                                    | See values, combination of connections 3  |             |             |             |      |      |      |      |
| Thermocouple/mV sensor                               | See values, combination of connections 2  |             |             |             |      |      |      |      |

### Electrical Data

|                               |   |
|-------------------------------|---|
| Number of channels            | 8 or 4 Ex i inputs<br>(depends on operating mode)   |
| Operating mode                | 4-channel fast (joystick)<br>8 channel accurate   |
| Connection Ex i field signals | Pluggable, blue terminals, 16-pin, 2.5 mm <sup>2</sup> , screw type or cage clamp version with lock |

### Auxiliary Power

|                               |                                      |
|-------------------------------|--------------------------------------|
| Power supply connection       | BusRail types 9494                   |
| Auxiliary power version       | Intrinsically safe Ex ia via BusRail |
| Current consumption           | 42 mA                                |
| Max. power consumption        | 1 W                                  |
| Max. power dissipation inputs | 1 W                                  |

### Galvanic Isolation

|                                      |                              |
|--------------------------------------|------------------------------|
| Test voltage for galvanic separation | Acc. to standard EN 60079-11 |
|--------------------------------------|------------------------------|

## Remote I/O

### Remote I/O IS1+ Temperature input module

for Zone 1 Ex i

9482/32-08-11 Art. No. 217643



#### Galvanic Isolation

|                                   |             |
|-----------------------------------|-------------|
| Auxiliary power/system components | ≥ 1500 V AC |
| I/O module / I/O module           | ≥ 500 V AC  |
| I/O channels/system components    | ≥ 500 V AC  |
| I/O channels / ground (PA)        | ≥ 500 V AC  |

#### Input

|  |  |
|--|--|
| Sensor type 1  | Resistance temperature detector<br>Resistance transmitter  |
| Resistance range                                     | 0 – 10 kΩ  |
| Measuring current                                    | < 200 μA multiplexed   |
| Accuracy of measurement                              | ± 1% (4-channel fast)<br>0.025% (8-channel accurate)   |
| Linearity 1 (adjustable parameters)                  | Resistance-linear<br>Temperature-linear  |
| Sensor type 2  | Thermocouples<br>mV transmitter  |
| Connection type 2                                    | 2-wire circuits  |
| Signal range of inputs                               | -10 ... +100 mV  |
| Linearity 2 (adjustable parameters)                  | Voltage-linear<br>Temperature-linear   |
| Max. permissible total line resistance per conductor | 100 ohm per core   |
| Input resistance                                     | Max. 10 mΩ per channel   |
| Compensation of reference junctions                  | Internal (adjustable parameters)<br>External 3-wire circuit  |
| Min. input measuring range                           | -40 °C   |
| Max. input measuring range                           | +80 °C   |
| Resolution   | 0.1 K  |
| Accuracy of measurement at reference junctions       | Internal: 0.025%<br>External: depends on the sensor type, see connectable resistance temperature detectors |
| Temperature deviation                                | ±2 K for thermocouples with internal compensation  |

# Remote I/O

## Remote I/O IS1+ Temperature input module

for Zone 1 Ex i

9482/32-08-11 Art. No. 217643



| Connectable<br>resistance temperature detectors/<br>resistance transmitters | Type   |                       | Reference  | Measuring range<br>(ITS-90)     | Average<br>measurement<br>discrimination                |                  |
|---|--|-----------------------|--|---------------------------------|---|------------------|
|   |  | Pt100                 |  | IEC 60751                       | -200 to +850 °C   | 0.1 K            |
|   | Pt500  |                       | IEC 60751  | -200 to +850 °C                 | 0.1 K   |                  |
|   | Pt1000                                       |                       | IEC 60751  | -200 to +850 °C                 | 0.1 K   |                  |
|   | Ni100  |                       | DIN 43760  | -60 to +180 °C                  | 0.1 K   |                  |
|   | Ni500  |                       | DIN 43760  | -60 to +180 °C                  | 0.1 K   |                  |
|   | Ni1000                                       |                       | DIN 43760  | -60 to +180 °C                  | 0.1 K   |                  |
|   | Pt46   |                       | GOST 6651-94                                     | -200 to +1100 °C                | 0.15 K  |                  |
|   | Pt50   |                       | GOST 6651-94                                     | -200 to +1100 °C                | 0.15 K  |                  |
|   | Pt100  |                       | GOST 6651-94                                     | -200 to +1100 °C                | 0.1 K   |                  |
|   | Cu53   |                       | GOST 6651-94                                     | -50 to +180 °C                  | 0.1 K   |                  |
|   | M50  |                       | GOST 6651-94                                     | -200 to +200 °C                 | 0.15 K  |                  |
|   | M100   |                       | GOST 6651-94                                     | -200 to +200 °C                 | 0.1 K   |                  |
|   | Resistance trans-<br>mitter<br>(3-conductor) |                       | --   | 0 to 500 Ω                      | 0.02 Ω  |                  |
|   | Resistance trans-<br>mitter<br>(3-conductor) |                       | --   | 0 to 2.5 kΩ                     | 0.10 Ω  |                  |
|   | Resistance trans-<br>mitter<br>(3-conductor) |                       | --   | 0 to 5 kΩ                       | 0.20 Ω  |                  |
|   | Resistance trans-<br>mitter<br>(3-conductor) |                       | --   | 0 to 10 kΩ                      | 0.4 Ω   |                  |
|   | Resistance trans-<br>mitter<br>(3-conductor) |                       | --   | -200 to +850 °C<br>500 to 10 kΩ | 0.1 K   |                  |
|   | Resistance trans-<br>mitter<br>(3-conductor) |                       | --   |                                 |   |                  |
|   | Joystick (4-conductor)                       |                       |  |                                 |   |                  |
| Reaction time   | Type   | Type of<br>connection | Operating mode                                   |                                 | Operating mode  |                  |
|   |  |                       | 4 channel rapid<br>Error monitoring<br>Activated | Deactivated                     | 8 channel precise<br>Error monitoring<br>Activat-<br>ed | Deactivat-<br>ed |
|   | RTD  | 2-conductor           | 400 ms   | 400 ms                          | 750 ms  | 720 ms           |
|   | RTD  | 3-conductor           | 400 ms   | 400 ms                          | 750 ms  |                  |
|   | RTD  | 4-conductor           | 400 ms   | 400 ms                          | 750 ms  |                  |
|   | R  | 2-conductor           | 400 ms   | 400 ms                          | 750 ms  | 720 ms           |
|   | R  | in R                  | 90 ms  | 70 ms                           | 750 ms  |                  |
|   | R  | 3-conductor           | 400 ms   | 400 ms                          | 750 ms  |                  |
|   | R  | in %                  | 90 ms  | 70 ms                           | 750 ms  |                  |
|   |  | 4-conductor<br>in R   |  |                                 |   |                  |
|   |  | 4-conductor<br>in %   |  |                                 |   |                  |

To achieve the times with "error control deactivated", the error control must be "OFF" for all channels. As soon as the error control is "ON" for just one channel, the times for "error control activated" apply.

# Remote I/O

## Remote I/O IS1+ Temperature input module

for Zone 1 Ex i

9482/32-08-11 Art. No. 217643



| Connectable thermocouples/mV sensors | Type        | Reference        | Measuring range (ITS-90) | Average measurement discrimination | Average error of measurement based on measuring range |
|--------------------------------------|-------------|------------------|--------------------------|------------------------------------|---|
|                                      | B           | IEC 60584-1      | -400 to +1800 °C         | 0.25 K                             | 0.1%  |
| E                                    | IEC 60584-1 | -200 to +1000 °C | 0.1 K                    | 0.013%                             |   |
| J                                    | IEC 60584-1 | -200 to +1200 °C | 0.1 K                    | 0.014%                             |   |
| K                                    | IEC 60584-1 | -200 to +1370 °C | 0.1 K                    | 0.02%                              |   |
| N                                    | IEC 60584-1 | -200 to +1300 °C | 0.1 K                    | 0.02%                              |   |
| R                                    | IEC 60584-1 | -50 to +1767 °C  | 0.2 K                    | 0.05%                              |   |
| S                                    | IEC 60584-1 | -50 to +1767 °C  | 0.2 K                    | 0.053%                             |   |
| T                                    | IEC 60584-1 | -200 to +400 °C  | 0.1 K                    | 0.042%                             |   |
| L                                    | DIN 43710   | -200 to +900 °C  | 0.1 K                    | 0.027%                             |   |
| U                                    | DIN 43710   | -200 to +600 °C  | 0.1 K                    | 0.038%                             |   |
| XK                                   | GOST 8,585  | -50 to +800 °C   | 0.1 K                    | 0.02%                              |   |
| mV                                   | --          | 0 to +100 mV     | 3.6 µV                   | 0.01%                              |   |

| Reaction time               | Type of connection | Operating mode  |                  | Operating mode    |                  |
|-----------------------------|--------------------|-----------------|------------------|-------------------|------------------|
|                             |                    | 4 channel rapid | Error monitoring | 8 channel precise | Error monitoring |
|                             |                    | Activated       | Deactivated      | Activated         | Deactivated      |
| Thermocouple<br>0 to 100 mV | 2-conductor        | 500 ms          | 450 ms           | 800 ms            | 750 ms           |
|                             | 2-conductor        | 500 ms          | 450 ms           | 800 ms            | 800 ms           |

To achieve the times with "error control deactivated", the error control must be "OFF" for all channels. As soon as the error control is "ON" for just one channel, the times for "error control activated" apply.

### Device Specific Data

|                                  |   |
|----------------------------------|---|
| Diagnostics message module       | OFF<br>ON   |
| Selection reference junction     | Internal/external 3-conductor   |
| External reference junction type | PT1000<br>PT100 GOST<br>PT100   |
| Sensor type                      | See table (connectable sensors)   |
| Type of connection               | 2-, 3- and 4-wire circuit   |
| Line fault monitoring            | OFF<br>ON   |
| Input behaviour in case of error | hold last value   |
| Retrievable parameters           | Hardware revision<br>Manufacturer<br>Serial number<br>Software revision<br>Type |
| LED module requires maintenance  | "M/S" LED, blue   |
| LED operating conditions         | "RUN" LED, green  |
| LED channel error                | LED for each channel, red   |

# Remote I/O

## Remote I/O IS1+ Temperature input module for Zone 1 Ex i

9482/32-08-11 Art. No. 217643



### Device Specific Data

|                                  |   |
|----------------------------------|---|
| Module status and alarms         | Primary/redundant internal bus error<br>No response from IOM<br>Configuration different from module<br>Hardware error<br>Overtemperature<br>Slot error<br>Module requires maintenance |
| Signal status bit                | 1 = Signal valid<br>0 = Signal interrupted  |
| Wire breakage input              | Thermocouples > 1000 ohm<br>Resistance transmitter > 100 Ω<br>Resistance thermometer > 100 ohm<br>mV transmitter > 1000 ohm   |
| Short circuit input              | Resistance transmitter < 15 ohm<br>Res.temp. detector < 15 ohm  |
| Measuring range                  | Shortfall<br>Overshoot  |
| Influence of ambient temperature | 0,025 % / 10 K  |

### Diagnostics

|                 |                |
|-----------------|----------------|
| LED group error | "ERR" LED, red |
|-----------------|----------------|

### Ambient Conditions

|                               |  |
|-------------------------------|--|
| Ambient temperature           | -40°C ... +75°C  |
| Ambient temperature           | -40°F ... +167°F   |
| Storage temperature           | -40°C ... +80°C  |
| Storage temperature           | -40°F ... +176°F   |
| Max. operating altitude       | < 2000 m   |
| Max. relative humidity        | 95% (without condensation)   |
| Shock (semi-sinusoidal)       | (IEC EN 60068-2-27)<br>15 g (3 shocks per axis and direction)  |
| Vibration (sinusoidal)        | (IEC EN 60068-2-6)<br>Frequency range 2 to 13.2 Hz Amplitude 1 mm (peak value)<br>Frequency range 13.2 to 100 Hz Acceleration amplitude 0.7 g                                    |
| Electromagnetic compatibility | Tested to the following standards and regulations: EN 61326-1 (2006) IEC 61000-4-1 to 61000-4-6, NAMUR NE 21<br>0.1 % (8 channel precise) under strong electromagnetic influence |
| Note                          | (observe operating instructions)   |

### Mechanical Data

|                                       |                   |
|---------------------------------------|-------------------|
| Degree of protection (IP) (IEC 60529) | IP20              |
| Module enclosure                      | Polyamide 6GF     |
| Fire resistance (UL 94)               | V2                |
| Pollutant class                       | Corresponds to G3 |
| Width                                 | 96.5 mm           |
| Width, inches                         | 3.8 in            |
| Height                                | 67 mm             |
| Length                                | 128 mm            |
| Length in inches                      | 5.04 in           |
| Mounting depth in inches              | 2.64 in           |
| Weight                                | 275 g             |

# Remote I/O

## Remote I/O IS1+ Temperature input module

for Zone 1 Ex i


9482/32-08-11 Art. No. 217643



### Mechanical Data


|                                |                           |
|--------------------------------|---------------------------|
| Weight                         | 0.61 lb                   |
| <b>Mounting / Installation</b> |                           |
| Mounting orientation           | Vertical<br>Horizontal    |
| Connection type 1              | 2-, 3- and 4-wire circuit |

### Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations







### Accessories

#### External reference junction

|  |   | Art. No. |
|--|---|----------|
|  | External reference junction for 2 x thermocouple (1 x Pt100 for 2-, 3- or 4-wire connection) integrated into the 4-pin terminal block. Mounted on a DIN rail. | 160675   |

#### Pluggable terminal

|  |   | Art. No. |
|--|---|----------|
|  | 2.5 mm <sup>2</sup> with lock, 16-pin, screw connector, blue, for connecting the field signals to I/O modules, for intrinsically safe field circuits<br>Labelling: 1 to 16<br>Note: A second terminal is additionally required for I/O module Series 9470 and 9482<br>Labelling: 17 to 32                           | 162702   |
|  | 2.5 mm <sup>2</sup> with lock, 16-pin, screw connector, blue, for connecting the field signals to I/O modules, for intrinsically safe field circuits<br>Labelling: 17 to 32   | 162718   |
|  | 2.5 mm <sup>2</sup> with lock, 16-pin, spring clamp connection, blue, for connecting the field signals to I/O modules, for intrinsically safe field circuits, incl. test jacks<br>Labelling: 1 to 16<br>Note: A second terminal is additionally required for I/O module Series 9470 and 9482<br>Labelling: 17 to 32 | 162695   |
|  | 2.5 mm <sup>2</sup> with lock, 16-pin, spring clamp connection, blue, for connecting the field signals to I/O modules, for intrinsically safe field circuits, incl. test jacks<br>Labelling: 17 to 32   | 162716   |







# Remote I/O

## Remote I/O IS1+ Temperature input module

for Zone 1 Ex i

9482/32-08-11 Art. No. 217643



| Partition  |   | Art. No. |
|--|---|----------|
|    | For mounting between intrinsically safe and non-intrinsically safe connections between I/O modules to maintain a tight string length of 50 mm   | 220101   |
| Resistor error message suppression   |   | Art. No. |
|    | The resistors are used to suppress error messages for unused I/O channels<br>Resistance value: 62R/0.5 W<br>Suitable for: AOM 9468; UMH 9469; DIOM 9472; TIM 9482   | 244912   |
| Warning label  |   | Art. No. |
|    | "Clean modules only with a damp cloth."   | 162796   |
| DIN A4 sheet   |   | Art. No. |
|   | For label plate on I/O modules; 6 plates per sheet;<br>IS Wizard printout; packaging unit = 20 sheets   | 162832   |
| Labelling strips   |   | Art. No. |
|  | "FB Addr ... Mod No ..." for pluggable terminal, 26 pieces on the sheet   | 162788   |
| Vibration bracket set  |   | Art. No. |
|  | When installed in environments with extreme vibration (> 0.7 g and max. 4 g), the 9490 vibration brackets may be used as an additional measure and provide mechanical stability for the individual modules.<br>For mounting: All I/O modules, except 9477/12 and 9478<br>Number of brackets in a set: 8<br>Screws (item no. 275516) must be ordered separately. | 271920   |
| Set of screws  |   | Art. No. |
|  | Set of M5 x 14 screws (self-tapping) for 9490 vibration brackets<br>Number of screws in a set: 25   | 275516   |

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.