

ControlLogix 5570 Standard and Conformal Coated Controllers

Features - ControlLogix 5570 Standard and Conformal Coated Controllers

Feature	1756-L71, 1756-L71K, 1756-L72, 1756-L72K, 1756-L73, 1756-L73K, 1756-L74, 1756-L74K, 1756-L75, 1756-L75K
Controller tasks	<ul style="list-style-type: none"> • 32 tasks, including a combination of one continuous, periodic, and event tasks • 32 programs/tasks prior to RSLogix 5000® programming software, version 15.01.00 • 100 programs/task beginning with RSLogix 5000 programming software, version 15.01.00 • 1000 programs/task beginning with Logix Designer application, version 24.00.00
Built-in communication ports	1-port USB ⁽¹⁾
Communication options	<ul style="list-style-type: none"> • EtherNet/IP • ControlNet • DeviceNet • Data Highway Plus • Remote I/O • SERCOS • Third-party process and device networks
USB port communication	Programming, configuration, firmware update, and online edits only
Controller connections supported max ⁽²⁾	500
Network connections, per network module	<ul style="list-style-type: none"> • 1000 I/O; 528 EtherNet/IP; 512 TCP (1756-EN4TR) • 256 EtherNet/IP; 128 TCP (1756-EN2x) • 128 EtherNet/IP; 64 TCP (1756-ENBT) • 100 ControlNet (1756-CN2/A) • 40 ControlNet (1756-CNB/D, 1756-CNB/E) • 128 ControlNet (1756-CN2/B)
Controller redundancy	Full support
Integrated motion	<ul style="list-style-type: none"> • SERCOS interface • Analog options (encoder input, LDT input, SSI input) • Integrated Motion on the EtherNet/IP network
Programming languages	<ul style="list-style-type: none"> • Relay ladder logic • Structured text • Function Block Diagram • Sequential function chart (SFC)

(1) The USB port is intended for temporary local programming purposes only and not intended for permanent connection. Do not use the USB port in hazardous locations.

(2) ControlLogix 5570 controllers use connections to establish communication links between devices. For more information on how to use and calculate connections, see the ControlLogix System User Manual, publication [1756-UM001](#).

Technical Specifications - ControlLogix 5570 Standard and Conformal Coated Controllers

Attribute	1756-L71, 1756-L71K	1756-L72, 1756-L72K	1756-L73, 1756-L73K	1756-L74, 1756-L74K	1756-L75, 1756-L75K
User memory	2 MB	4 MB	8 MB	16 MB	32 MB
I/O memory	0.98 MB				
Nonvolatile memory storage	1 GB Secure Digital (SD) card (1784-SD1), ships pre-installed in the controller ⁽¹⁾				
Digital I/O max	128,000				
Analog I/O max	4000				
Total I/O max	128,000				
Energy storage module	<ul style="list-style-type: none"> 1756-ESMCAP, 1756-ESMCAPK capacitor energy storage module (removable, ships installed with every controller) 1756-ESMNSE, 1756-ESMNSEK capacitor energy storage module (removable, no residual WallClockTime power backup) 1756-ESMNRM, 1756-ESMNRMK capacitor energy storage module (non-removable, helps prevent USB connection and SD card use to help secure the controller) 				
Current draw @ 1.2V DC	5 mA				
Current draw @ 5.1V DC	800 mA				
Power dissipation	2.5 W				
Thermal dissipation	8.5 BTU/hr				
Isolation voltage	30V (continuous), basic insulation type, USB port-to-system Compliant and tested according to IEC/UL 61010-1				
USB port ⁽²⁾	USB 2.0, full speed (12 Mbps)				
Weight approx	0.25 kg (0.55 lb)				
Slot width	1				
Module location	Chassis-based, any slot				
Chassis	1756-A4, 1756-A4K, 1756-A7, 1756-A7K, 1756-A10, 1756-A10K, 1756-A13, 1756-A13K, 1756-A17, 1756-A17K				
Power supply, standard	1756-PA50, 1756-PA50K, 1756-PA72, 1756-PA72K, 1756-PA75, 1756-PA75K, 1756-PB50, 1756-PB50K 1756-PB72, 1756-PB72K, 1756-PB75, 1756-PB75K, 1756-PC75, 1756-PH75				
Power supply, redundant	1756-PA75R, 1756-PA75RK, 1756-PB75R, 1756-PB75RK, 1756-PSCA2, 1756-PSCA2K				
Wire category ⁽³⁾	3 - on USB port				
Temperature code	T4				
Enclosure type rating	None (open-style)				

(1) Larger versions may be available. See [Memory Cards on page 61](#).

(2) The USB port is intended for temporary local programming purposes only and not intended for permanent connection. Do not use the USB port in hazardous locations.

(3) Use this conductor category information to plan conductor routing. See Industrial Automation Wiring and Grounding Guidelines, publication [1770-4.1](#).

Environmental Specifications - ControlLogix 5570 Standard and Conformal Coated Controllers

Attribute	1756-L71, 1756-L72, 1756-L73, 1756-L74, 1756-L75	1756-L71K, 1756-L72K, 1756-L73K, 1756-L74K, 1756-L75K
Temperature, operating IEC 60068-2-1 (Test Ae, Operating Cold), IEC 60068-2-2 (Test Be, Operating Dry Heat), IEC 60068-2-14 (Test Nb, Operating Thermal Shock)	0 °C ≤ Ta ≤ +60 °C (+32 °F ≤ Ta ≤ +140 °F)	
Temperature, nonoperating IEC 60068-2-1 (Test Ab, Unpackaged Nonoperating Cold), IEC 60068-2-2 (Test Bb, Unpackaged Nonoperating Dry Heat), IEC 60068-2-14 (Test Na, Unpackaged Nonoperating Thermal Shock)	-40...+85 °C (-40...+185 °F)	
Relative humidity IEC 60068-2-30 (Test Db, Unpackaged Damp Heat)	5...95% noncondensing	
Conformal coated	No	Yes
Corrosive Atmosphere ASTM B845-97 Method K Accelerated Test (20-Day Exposure)	-	Severity Level G3 ⁽¹⁾ per ANSI/ISA 71.04-2013, Airborne Contaminants—Gases Severity Level CX ⁽¹⁾⁽²⁾ per IEC 60721-3-3:2019, Chemically Active Substances
Vibration	IEC 60068-2-6 (Test Fc, Operating)	
Shock, operating	IEC 60068-2-27 (Test Ea, Unpackaged Shock)	
Shock, nonoperating	IEC 60068-2-27 (Test Ea, Unpackaged Shock)	
Emissions	IEC 61000-6-4	
ESD immunity	IEC 61000-4-2	
Radiated RF immunity	IEC 61000-4-3	
Conducted RF Immunity	IEC 61000-4-6 (Not applicable: USB is a temporary programming port.)	

(1) Once the factory packaging seal is broken, plugs or covers must be installed in all unoccupied ports or slots for the product to maintain its corrosive atmosphere rating.
 (2) Up to 86.4 g/(m²-yr), mass loss of copper due to corrosion.