



Main

| | |
|------------------------------|------------------------------|
| Range of Product | Harmony XK |
| Product or Component Type | Complete joystick controller |
| Product Specific Application | Light hoisting applications |

Complementary

| | |
|---|--|
| Device short name | XKB |
| Bezel material | Metal |
| Fixing collar material | Metal |
| Sale per indivisible quantity | 1 |
| Protective treatment | TC |
| Ambient Air Temperature for Storage | -40...158 °F (-40...70 °C) |
| Ambient Air Temperature for Operation | -4...158 °F (-20...70 °C) |
| Overvoltage category | Class I IEC 61140 |
| IP degree of protection | IP54 IEC 60529 IP20 IEC 60529 |
| Standards | UL 508 CSA C22.2 No 14 EN/IEC 60947-5-1 |
| Product Certifications | CSA UL CCC RRS |
| Contact code designation | A300 Q300 |
| Operator position information | All positions |
| Operator profile | Handle with zero position mechanical interlock |
| Notch per direction | 1...3 12°-20°-28° for each direction |
| Mechanical durability | 1000000 cycles |
| Vibration resistance | 6 gn 1...70 Hz)IEC 60068-2-6 |
| Shock resistance | 20 gn 11 ms) IEC 60068-2-27 |
| Connections - terminals | Captive screw clamp terminals, <= 2 x 1.5 mm ² with cable end Captive screw clamp terminals, <= 1 x 2.5 mm ² without cable end Captive screw clamp terminals, >= 1 x 0.5 mm ² |
| Short-circuit protection | 10 A cartridge fuse gG EN/IEC 60947-5-1 |
| [Ith] conventional free air thermal current | 10 A EN/IEC 60947-5-1 10 A CSA C22.2 No 14 10 A UL 508 |
| [Ui] rated insulation voltage | 500 V 3)IEC 60947-1 |

Ordering and shipping details

| | |
|-----------------------|----------------------------------|
| Category | 22474-PUSHBUTTON,CRANE JOYSTICKS |
| Discount Schedule | I |
| GTIN | 785901895480 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 29.98 oz (850.0 g) |
| Returnability | No |
| Country of origin | FR |

Packing Units

| | |
|------------------------|--------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 6.00 in (15.24 cm) |
| Package 1 width | 6.50 in (16.51 cm) |
| Package 1 Length | 9.50 in (24.13 cm) |

Offer Sustainability

| | |
|----------------------------|--|
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Schneider Electric:](#)

[XKBA34207](#)