

9.4.3 Output Modules

24 V DC	> 24 V	safety related AK 1...6	LS & LB	safe isolation	Load	Space requirement	Type
•				•	≤ 0.5 A	4 HE	F 3322
•		•		•	≤ 0.5 A	4 HE	F 3330
•		•	•	•	≤ 0.5 A	4 HE	F 3331
•				•	≤ 2 A	4 HE	F 3332
•		•		•	≤ 2 A	4 HE	F 3333
•		•	•	•	≤ 2 A	4 HE	F 3334
	•			•	≤4 A, ≤60 V	4 HE	F 3422
		•		•	0...20 mA	4 HE	F 6705
				•	0...20 mA	4 HE	F 6706

LS = line short circuit monitoring
 LB = line break monitoring
 TE = units width

9.4.4 Current Distribution Modules and Subracks

F 7133 4-fold power distribution with fuse monitoring

9.4.5 Additional Devices

F 7131 Power supply monit. with buffer batteries for H51q

H 7013 Power supply filtre

9.5 Communication Modules

F 8621A H51q coprocessor module

F 8625 Communication module for ethernet communication for H51q

F 8626 Communication module for Profibus-DP communication for H51q

9.6 Modules for I/O Bus Coupling

F 7553 Coupling module for H51q

9.7 Bus connection modules for HIBUS

H 7505 data signal converter RS 232C/ 20 mA/ 2-wire/ 4wire (HIBUS)

H 7506 Bus terminal module for 2 wire-buses