



SIMATIC S7-1200, Digital output SM 1222, 16 DO, 24 V DC, transistor 0.5 A

General information	
Product type designation	SM 1222, DQ 16x24 V DC/0.5 A
Supply voltage	
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
from backplane bus 5 V DC, max.	140 mA
Power loss	
Power loss, typ.	2.5 W
Digital outputs	
Number of digital outputs	16
• in groups of	1
Short-circuit protection	No; to be provided externally
Limitation of inductive shutdown voltage to	typ. (L+) -48 V
Switching capacity of the outputs	
• with resistive load, max.	0.5 A
• on lamp load, max.	5 W
Output voltage	
• Rated value (DC)	24 V
• for signal "0", max.	0.1 V; with 10 kOhm load
• for signal "1", min.	20 V DC
Output current	
• for signal "1" rated value	0.5 A
• for signal "0" residual current, max.	10 µA
Output delay with resistive load	
• "0" to "1", max.	50 µs
• "1" to "0", max.	200 µs
Total current of the outputs (per group)	
horizontal installation	
— up to 50 °C, max.	8 A; Current per mass
Cable length	
• shielded, max.	500 m
• unshielded, max.	150 m
Interrupts/diagnostics/status information	
Alarms	
• Diagnostic alarm	Yes
Diagnostics indication LED	
• for status of the outputs	Yes
Potential separation	
Potential separation digital outputs	

• between the channels, in groups of • between the channels and backplane bus	1 500 V AC
Degree and class of protection	
IP degree of protection	IP20
Standards, approvals, certificates	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
cULus	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
Marine approval	Yes
Ambient conditions	
Free fall	
• Fall height, max.	0.3 m; five times, in product package
Ambient temperature during operation	
• min. • max. • horizontal installation, min. • horizontal installation, max. • vertical installation, min. • vertical installation, max. • permissible temperature change	-20 °C 60 °C -20 °C 60 °C -20 °C 50 °C 5°C to 55°C, 3°C / minute
Ambient temperature during storage/transportation	
• min. • max.	-40 °C 70 °C
Air pressure acc. to IEC 60068-2-13	
• Storage/transport, min. • Storage/transport, max.	660 hPa 1 080 hPa
Relative humidity	
• Operation at 25 °C without condensation, max.	95 %
connection method	
required front connector	Yes
Mechanics/material	
Enclosure material (front)	
• Plastic	Yes
Dimensions	
Width	45 mm
Height	100 mm
Depth	75 mm
Weights	
Weight, approx.	220 g

last modified:

3/12/2024 