


AMIKON TECHNICAL INTELLIGENCE

Product Data Sheet

Bently Nevada 21000-28-05-00-035-01-02
Aluminum proximity probe housing assembly with 3300 XL 8 mm probe



PRODUCT	THREAD	TOTAL LENGTH	SYSTEM
21000 Proximity Probe Housing Assembly	3/4-14 NPT	0.5 m probe cable	21000 Proximity Probe Housing Assembly

Bently Nevada 21000-28-05-00-035-01-02 is a Aluminum proximity probe housing assembly with 3300 XL 8 mm probe used as the sensing or signal component in the matching 21000 Proximity Probe Housing Assembly system. Complete measurement requires compatible system components and the exact ordered electrical or loop configuration.

01 CURRENT PAGE PARAMETERS

Product Model	21000-28-05-00-035-01-02
Product Parameters	Aluminum proximity probe housing assembly with 3300 XL 8 mm probe; 3/4-14 NPT; aluminum housing;
Tariff Code	9031809090
Place of shipment	Xiamen, China
Estimated Shipping Size	14.0 x 11.5 x 11.5 cm
Product Type	21000 Proximity Probe Housing Assembly
Case Thread	3/4-14 NPT
Unthreaded Length	No standoff adapter
Total Length	0.5 m probe cable
Cable and Connector	One explosion-proof fitting and one plug
Estimated Probe Temperature Range	Refer to official manufacturer datasheet
Series-level Typical Weight	1.18 kg

Source scope: official Bently Nevada 141600 Rev. AC, current product record, tariff and shipment fields. Technical configuration is limited to this exact model.

02 ORDERING CODE VERIFICATION

21000	Aluminum proximity probe housing assembly
28	3300 XL 8 mm probe with selectable hazardous-area approvals
05	0.5 m probe cable
00	No standoff adapter
035	3.5 in probe penetration
01	One explosion-proof fitting and one plug
02	3/4-14 NPT mounting thread

03 SYSTEM ROLE AND APPLICATIONS

The ordered 21000-28-05-00-035-01-02 configuration is used only with the compatible 21000 Proximity Probe Housing Assembly system. Maintain the specified system length, mounting, connector or output, and approval option.

- External mounting of proximity probes
- Fluid-film bearing vibration measurement installations
- Axial shaft position measurement installations
- Hazardous-area machinery monitoring installations

04 OFFICIAL INSTALLATION FACTS

- Use the specified 3/4-14 NPT mounting configuration.
- Maintain the ordered 0.5 m probe cable system length.
- Preserve One explosion-proof fitting and one plug and protect all connections.
- Use the manufacturer drawing and controlled procedure for installation.

05 OFFICIAL DOCUMENTATION

[21000 Proximity Probe Housing Assembly System Datasheet - 141600 Rev. AC](#)

Controlled references remain in the official data sheet and manufacturer documentation. Obtain current revisions through the manufacturer media library.

AMIKON PRODUCT SUPPORT

Amikon Limited

INFO@AMIKON.CN