

AMIKON TECHNICAL INTELLIGENCE

Product Data Sheet

Bently Nevada 330101-30-61-10-02-05
3300 XL 8 mm standard-mount proximity probe



PRODUCT	THREAD	TOTAL LENGTH	SYSTEM
3300 XL 8 mm	3/8-24 UNF	1.0 m	3300 XL 8 mm

Bently Nevada 330101-30-61-10-02-05 is a 3300 XL 8 mm standard-mount proximity probe used as the sensing or signal component in the matching 3300 XL 8 mm system. Complete measurement requires compatible system components and the exact ordered electrical or loop configuration.

01

CURRENT PAGE PARAMETERS

Product Model	330101-30-61-10-02-05
Product Parameters	3300 XL 8 mm standard-mount proximity probe; 3/8-24 UNF; without armor
Tariff Code	9031809090
Place of shipment	Xiamen, China
Estimated Shipping Size	1.5 x 1.3 x 125 cm
Product Type	3300 XL 8 mm
Case Thread	3/8-24 UNF
Unthreaded Length	3.0 in
Total Length	1.0 m
Cable and Connector	ClickLoc, standard cable
Estimated Probe Temperature Range	Refer to official manufacturer datasheet
Series-level Typical Weight	0.05 kg

Source scope: official Bently Nevada 141194 Rev. AM, current product record, tariff and shipment fields. Technical configuration is limited to this exact model.

02 ORDERING CODE VERIFICATION

330101	3300 XL 8 mm standard-mount proximity probe
30	3.0 in unthreaded length
61	6.1 in overall case length
10	1.0 m total length
02	ClickLoc, standard cable
05	CSA, ATEX and IECEx

03 SYSTEM ROLE AND APPLICATIONS

The ordered 330101-30-61-10-02-05 configuration is used only with the compatible 3300 XL 8 mm system. Maintain the specified system length, mounting, connector or output, and approval option.

- Radial vibration measurement on fluid-film bearing machines
- Axial shaft position measurement
- Keyphasor phase reference measurement
- Shaft speed measurement

04 OFFICIAL INSTALLATION FACTS

- Use the specified 3/8-24 UNF mounting configuration.
- Maintain the ordered 1.0 m system length.
- Preserve ClickLoc, standard cable and protect all connections.
- Use the manufacturer drawing and controlled procedure for installation.

05 OFFICIAL DOCUMENTATION

[3300 XL 8 mm System Datasheet - 141194 Rev. AM](#)

Controlled references remain in the official data sheet and manufacturer documentation. Obtain current revisions through the manufacturer media library.

AMIKON PRODUCT SUPPORT

Amikon Limited

INFO@AMIKON.CN