

AMIKON TECHNICAL DOCUMENTATION

Product Data Sheet

Bently Nevada CB2W100-064

64 ft splash-proof interconnect cable for two-wire transducers

LENGTH	CABLE	CONDUCTOR	MONITOR END
64 ft / 19.5 m	Shielded	22 AWG	Blunt cut

Bently Nevada CB2W100-064 provides a 64 ft shielded connection for compatible two-wire vibration transducers. Its splash-proof overmolded boot protects the sensor-end connection, while the blunt-cut monitor end allows termination within the documented measurement-system wiring arrangement.

01

VERIFIED TECHNICAL DATA

Cable length	64 ft, approximately 19.5 m
Transducer connection class	Two-wire transducer interconnect
Conductor size	22 AWG (0.382 mm2 as published)
Screen construction	Shielded cable
Sensor-end protection	Splash-proof overmolded boot
Monitor-end preparation	Blunt cut
Cable temperature rating	-50 to +200 C
200350 sealing limitation	Not recommended because O-ring seal is unsuitable

Official basis: 185M2670 Rev. A, p. 7; 105M0340 Rev. AD, p. 12. No unverified packing dimensions, shipping weight or hardware revision is stated.

02 APPLICATION & COMPATIBILITY

- Interconnect component for compatible two-wire transducers; not a calibrated 3300 XL probe extension cable.
- Do not select CB2W100 for the 200350 accelerometer. The manufacturer states that its O-ring does not form a proper seal.
- The cable has a published -50 to +200 C range. The connected transducer, sealing arrangement and monitor can impose narrower limits.
- Use the documented sensor connection and monitor termination. No pinout, tightening torque or minimum bend radius is invented in this reference.

03 SERIES APPLICATION CONTEXT

- Interconnection for stator-frame low-frequency vibration measurements
- Two-wire vibration signal paths on essential mill machinery
- Machine-casing monitoring connections in manufacturing plants

These are applications of the officially documented monitoring families, not claims that this exact cable was installed in a named project. Verify the selected sensor and interface for each measurement point.

04 OFFICIAL DOCUMENTATION

Low Frequency Velocity Transducer System - 185M2670 Rev. A

2300 Vibration Monitors - 105M0340 Rev. AD

The eight parameter rows cover the independently published cable facts. Additional rows are not added by repeating values or borrowing sensor performance data.

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM