

AMIKON LIMITED

TRICONEX SAFETY SYSTEMS

Product Data Sheet

9662-110

Digital output panel

PRODUCT NUMBER	SYSTEM PLATFORM	FIELD POINTS	WEIGHT
9662-110	Tricon v9–v11	16 channels	0.52 kg

Triconex 9662-110 is a Digital output panel used with the Tricon safety instrumented system. Verify the complete product identity and installed configuration before replacement.

01

VERIFIED TECHNICAL DATA

Panel Type	Non-commoned digital-output termination panel
Product Number	9662-110
System Platform	Tricon v9–v11
Field Points	16 channels
Nominal Signal Voltage	24 V DC
Compatible I/O Module	Tricon 3604E
External Termination Assembly	3000570-310
Required Interface Cable	4000094-310
Cable Standard Length	10 ft / 3.0 m
Point Arrangement	Individually wired non-commoned outputs

02 ADDITIONAL TECHNICAL DATA

Electrical Isolation	500 V DC
Operating Temperature	-40–70 °C
Storage Temperature	-55–85 °C
Relative Humidity	5–95% noncondensing
Mounting Method	DIN-rail external termination

03 PRODUCT IDENTITY AND FUNCTION

The exact 9662-110 identity describes a Digital output panel. Match its ratings, suffixes, connectors and system position with the installed Triconex equipment. Preserve approved configuration and maintenance records.

04 OFFICIAL APPLICATIONS

- Process safety and emergency shutdown maintenance
- Fire and gas protection system lifecycle support
- Exact-model replacement in documented Triconex configurations

05 SYSTEM AND COMMERCIAL REFERENCES

Product	9662-110
Manufacturer	Triconex / Schneider Electric
Origin	United States
HS reference	8538900000
Packed size	19.8 × 11.2 × 6 cm
Shipping weight	0.52 kg
Warranty	12 months from AMIKON

AMIKON PRODUCT SUPPORT

Amikon Limited
INFO@AMIKON.CN

AMIKONG.COM