

AMIKON TECHNICAL DOCUMENTATION

Product Data Sheet

Bently Nevada 330130-040-01-05

Armored Proximity Extension Cable



TYPE	REFERENCE	SCOPE	OPTIONS
Cable	141194	See table	Check order

330130-040-01-05 - Armored proximity extension cable. Use only the documented component configuration.

01

VERIFIED PRODUCT IDENTITY

Product model	330130-040-01-05
Extension length	4.0 m
Compatible transducer family	3300 XL 8 mm
Protective configuration	Armored; no connector protector
Approval option	05: multiple approvals
Conductor construction	75-ohm triaxial cable
Insulation	Fluoroethylene propylene (FEP)
Connector material	Gold-plated brass

Datasheet 141194 Rev. AL. Verify the complete supplied product identity.

02 TECHNICAL DATA

Minimum bend radius	25.4 mm
Maximum connector torque	0.565 N-m; finger tight recommended
Operating and storage temperature	-52 to +177 degrees C

03 APPLICATION AND CONFIGURATION

- Radial shaft vibration
- Axial thrust position
- Speed and phase channels
- Match documented component and system requirements
- Verify actual product markings before installation

04 OFFICIAL DOCUMENTATION

Datasheet 141194 Rev. AL

Selected manufacturer data applies to the identified component and documented conditions. Check the full ordering configuration. Consult the applicable installation instructions before selecting, installing or replacing equipment.

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM