

AMIKON TECHNICAL DOCUMENTATION

Product Data Sheet

Bently Nevada 330930-065-01-05

Armored Proximity Extension Cable



TYPE	REFERENCE	SCOPE	OPTIONS
Cable	147385	See table	Check order

330930-065-01-05 - Armored proximity extension cable. Use only the documented component configuration.

01

VERIFIED PRODUCT IDENTITY

Product model	330930-065-01-05
Extension length	6.5 m
Compatible transducer family	3300 XL NSv
Protective configuration	Armored; no connector protector
Approval option	05: multiple approvals
Conductor construction	75-ohm coaxial cable
Insulation	Fluoroethylene propylene (FEP)
Connector material	Gold-plated brass

Datasheet 147385 Rev. P. Verify the complete supplied product identity.

02 TECHNICAL DATA

Minimum bend radius	25.4 mm
Maximum connector torque	0.56 N-m; finger tight recommended
Operating and storage temperature	-52 to +177 degrees C

03 APPLICATION AND CONFIGURATION

- Restricted shaft access
- Compact compressor monitoring
- Compressor position measurement
- Match documented component and system requirements
- Verify actual product markings before installation

04 OFFICIAL DOCUMENTATION

Datasheet 147385 Rev. P

Selected manufacturer data applies to the identified component and documented conditions. Check the full ordering configuration. Consult the applicable installation instructions before selecting, installing or replacing equipment.

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM