

TRICONEX SAFETY SYSTEM

Product Data Sheet

8112

Remote expansion chassis

FUNCTION	FAMILY	ORIGIN	WEIGHT
Remote expansion chassis	Triconex safety system	United States	2.26 kg

Triconex 8112 is a Remote expansion chassis for the Triconex safety system. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

Product Class	Remote expansion chassis
System Platform	Tricon fault-tolerant controller
Mechanical Format	19-inch industrial rack assembly
Chassis Fabrication	Black zinc-plated welded steel
Overall Width	48.3 cm cabinet span
Overall Height	57.8 cm installed frame
Overall Depth	45.1 cm enclosure clearance
I/O Bus Architecture	Three isolated RS-485 channels
I/O Bus Rate	375 kbit/s triplicated transfer
Communication Bus Rate	2 Mbit/s module link

ADDITIONAL PRODUCT DATA

Expansion Ports	Six backplane bus connectors
Controller Keyswitch	RUN-PROGRAM-STOP-REMOTE selection
Module Retention	Mechanically keyed slot guides
Engineering Software	TriStation 1131 configuration
Safety Architecture	Triple modular redundant operation

OFFICIAL APPLICATIONS

- Safety control: Configured shutdown and process-protection logic
- Field integration: Documented input, output or communication circuits
- Lifecycle service: Diagnostics and controlled replacement testing

SYSTEM COMPATIBILITY

Match 8112 to the installed Triconex safety system, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

OFFICIAL SOURCES

[Tricon Technical Product Guide](#)

<https://www.se.com/ww/en/product-range/63717-triconex-safety-systems/>

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM