

AMIKON TECHNICAL DOCUMENTATION

Product Data Sheet

Bently Nevada 330104-00-06-50-02-00

Armored Metric Proximity Probe

THREAD	LENGTH	CONNECTOR	APPROVAL
M10 x 1	5 m	ClickLoc	00

330104-00-06-50-02-00 - Armored metric proximity probe.
Match mounting, target conditions and total electrical length to the documented 3300 XL 8 mm system.

01

VERIFIED PRODUCT IDENTITY

Product model	330104-00-06-50-02-00
Mounting thread	M10 x 1
Unthreaded length	0 mm
Overall case length	60 mm
Nominal total probe length	5 m
Lead protection	Stainless steel armor; FEP jacket
Connector and cable	ClickLoc; standard; no protector
Agency approval option	00: not required

Official source: Datasheet 141194 Rev. AM. Verify complete ordering options and installed system.

02 TECHNICAL DATA

Probe tip diameter	8.0 mm
Probe tip material	Polyphenylene sulfide (PPS)
Nominal probe DC resistance	8.73 ohms, +/-0.50; center to outer

03 APPLICATION AND CONFIGURATION

- Armored shaft vibration sensing
- Metric probe position channels
- Keyphasor and speed reference sensing
- Match the probe, extension cable and Proximito Sensor
- Verify target, mounting and supplied approval markings

04 OFFICIAL DOCUMENTATION

Datasheet 141194 Rev. AM

Series data applies under documented conditions. Verify the complete ordering configuration before selection or replacement. Consult the original manufacturer instructions for electrical length, target material and installation requirements.

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM