

SERIES 72 MODUTROL IV

Product Data Sheet

M7284A1038

Modutrol IV motor actuator

FUNCTION Modutrol IV motor actuator	FAMILY Series 72 Modutrol IV	ORIGIN United States	WEIGHT 3.4 kg
---	--	--------------------------------	-------------------------

Honeywell M7284A1038 is a Modutrol IV motor actuator for the Series 72 Modutrol IV. The values below are limited to the exact documented article.

01

VERIFIED TECHNICAL DATA

Supply Voltage	120 V AC
Control Input	4 to 20 mA
Torque Rating	75 lb-in / 8.5 N·m
Stroke Time	15 to 30 seconds
Rotation Range	90° factory setting
Adjustable Stroke	90° to 160° asymmetric
Auxiliary Switch	Not included
Wiring Method	Screw terminals
Power Consumption	15 VA nominal
Motor Series	Series 72 Modutrol IV

ADDITIONAL PRODUCT DATA

Mechanical Output	Rotary shaft drive
Application	Damper and valve positioning
Transformer	Internal supply transformer
Product Weight	7.5 lb / 3.4 kg
Commissioning	Stroke and feedback calibration

OFFICIAL APPLICATIONS

- Use the documented supply voltage: Apply M7284A1038 where supply voltage is 120 V AC. Confirm the installed hardware, field circuit and configuration before connection.
- Match the specified torque rating: Verify torque rating as 75 lb-in / 8.5 N-m together with the exact terminals, companion equipment and approved engineering record.
- Complete the commissioning: After installation, perform stroke and feedback calibration, review diagnostics and save the measured result before returning the equipment to service.

SYSTEM COMPATIBILITY

Match M7284A1038 to the installed Series 72 Modutrol IV, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

OFFICIAL SOURCES

[Honeywell industrial product documentation](#)

<https://automation.honeywell.com/>

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM