

AMIKON TECHNICAL DOCUMENTATION

Product Data Sheet

Bently Nevada 330101-00-52-10-12-05

Unarmored Imperial Proximity Probe

THREAD	LENGTH	CONNECTOR	APPROVAL
3/8-24 UNF-2A	1 m	ClickLoc	05

330101-00-52-10-12-05 - Unarmored imperial proximity probe.
Match mounting, target conditions and electrical length to the documented 3300 XL 8 mm system.

01

VERIFIED PRODUCT IDENTITY

Product model	330101-00-52-10-12-05
Mounting thread	3/8-24 UNF-2A
Unthreaded length	0.0 in
Overall case length	5.2 in
Nominal total probe length	1 m
Lead protection	Without armor
Connector and cable	ClickLoc; FluidLoc; no protector
Agency approval option	05: CSA, ATEX, IECEX; verify markings

Datasheet 141194 Rev. AM. Verify the complete supplied product identity.

02 TECHNICAL DATA

Probe tip diameter	8.0 mm
Probe tip material	Polyphenylene sulfide (PPS)
Nominal probe DC resistance	7.59 ohms, +/-0.50; center to outer

03 APPLICATION AND CONFIGURATION

- Unarmored shaft vibration sensing
- Imperial probe position channels
- Keyphasor and speed reference sensing
- Match documented component and system requirements
- Verify actual product markings before installation

04 OFFICIAL DOCUMENTATION

Datasheet 141194 Rev. AM

Selected manufacturer data applies to the identified component and documented conditions. Check the full ordering configuration. Consult the applicable installation instructions before selecting, installing or replacing equipment.

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM